



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Move-AppxPackage'

PS C:\Users\wahid> Get-Help Move-AppxPackage

NAME

Move-AppxPackage

SYNOPSIS

Moves a package from its current location to another appx volume.

SYNTAX

```
Move-AppxPackage [-Package] <System.String[]> [-Volume] <AppxVolume>  
[-Confirm] [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The `Move-AppxPackage` cmdlet moves a package from its current location to another AppxVolume . The new location must be a volume that Package Manager knows about and that's mounted. This cmdlet also moves your application data to the specified volume.

PARAMETERS

-Package <System.String[]>

Specifies an AppxPackage object or the full name of a package. This cmdlet moves the package that this parameter specifies.

`-Volume <AppxVolume>`

Specifies an AppxVolume object. The cmdlet moves the package to the volume that this parameter specifies.

`-Confirm <System.Management.Automation.SwitchParameter>`

Prompts you for confirmation before running the cmdlet.

`-WhatIf <System.Management.Automation.SwitchParameter>`

Shows what would happen if the cmdlet runs. The cmdlet isn't run.

`<CommonParameters>`

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<https://go.microsoft.com/fwlink/?LinkID=113216>).

-- Example 1: Move a package to a volume specified by a path --

```
Move-AppxPackage -Package "package1_1.0.0.0_neutral__8wekyb3d8bbwe" -Volume F:\
```

This command moves package that has the specified name to volume `F:`. This cmdlet also moves your app data.

--- Example 2: Move a package to a volume specified by an ID ---

```
$params = @{  
    Package = 'package1_1.0.0.0_neutral__8wekyb3d8bbwe'  
    Volume = '{d2a4d1f4-f45a-46f3-a419-160ab52af091}'  
}  
Move-AppxPackage @params
```

This command moves package that has the specified name to the volume that has the specified media ID. This cmdlet also moves your app data.

REMARKS

To see the examples, type: "get-help Move-AppxPackage -examples".

For more information, type: "get-help Move-AppxPackage -detailed".

For technical information, type: "get-help Move-AppxPackage -full".

For online help, type: "get-help Move-AppxPackage -online"