



**Full credit is given to all the above companies including the Operating System that this PDF file was generated!**

### **Windows PowerShell Get-Help on Cmdlet 'New-AzAppConfigurationStoreKey'**

**PS:>Get-HELP New-AzAppConfigurationStoreKey -Full**

#### **NAME**

New-AzAppConfigurationStoreKey

#### **SYNOPSIS**

Regenerates an access key for the specified configuration store.

#### **SYNTAX**

```
New-AzAppConfigurationStoreKey -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>] -Id  
<String> [-DefaultProfile <PSObject>] [-Break]  
[-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential  
<PSCredential>] [-ProxyUseDefaultCredentials]  
[-WhatIf] [-Confirm] [<CommonParameters>]
```

```
New-AzAppConfigurationStoreKey -InputObject <IAppConfigurationIdentity> -Id <String> [-DefaultProfile <PSObject>]  
[-Break] [-HttpPipelineAppend <SendAsyncStep[]>]  
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]  
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## DESCRIPTION

Regenerates an access key for the specified configuration store.

## PARAMETERS

-Name <String>

The name of the configuration store.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group to which the container registry belongs.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-SubscriptionId <String>

The Microsoft Azure subscription ID.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IAppConfigurationIdentity>

## Identity Parameter

To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

### -Id <String>

The id of the key to regenerate.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value            False

Accept pipeline input?    false

Accept wildcard characters? false

#### -HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required?            false

Position?            named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### -HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required?            false

Position?            named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required?            false

Position?            named

Default value

Accept pipeline input?    false

Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -WhatIf [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Confirm [<SwitchParameter>]

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkId=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.IAppConfigurationIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.AppConfiguration.Models.Api20220501.IApiKey

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help about\_Hash\_Tables.

**INPUTOBJECT <IAppConfigurationIdentity>: Identity Parameter**

[ConfigStoreName <String>]: The name of the configuration store.

[GroupName <String>]: The name of the private link resource group.

[Id <String>]: Resource identity path

[KeyValueName <String>]: Identifier of key and label combination. Key and label are joined by \$ character. Label is optional.

[Location <String>]: The location in which uniqueness will be verified.

[PrivateEndpointConnectionName <String>]: Private endpoint connection name

[ResourceGroupName <String>]: The name of the resource group to which the container registry belongs.

[SubscriptionId <String>]: The Microsoft Azure subscription ID.

----- EXAMPLE 1 -----

```
PS C:\>$keys = Get-AzAppConfigurationStoreKey -Name azpstest-appstore -ResourceGroupName azpstest_gp
```

```
New-AzAppConfigurationStoreKey -Name azpstest-appstore -ResourceGroupName azpstest_gp -Id $keys[0].id
```

#### RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.appconfiguration/new-azappconfigurationstorekey>