Windows PowerShell Get-Help on Cmdlet 'Remove-AzHealthcareFhirService'

PS:\>Get-HELP Remove-AzHealthcareFhirService -Full

NAME

   Remove-AzHealthcareFhirService

SYNOPSIS

   Deletes a FHIR Service.

SYNTAX

       Remove-AzHealthcareFhirService -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>]
-WorkspaceName <String> [-DefaultProfile <PSObject>] [-AsJob]

     [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru]
[-Proxy <Uri>] [-ProxyCredential <PSCredential>]

    [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]

     Remove-AzHealthcareFhirService -InputObject <IHealthcareApisIdentity> [-DefaultProfile <PSObject>] [-AsJob] [-Break]
[-HttpPipelineAppend <SendAsyncStep[]>]

     [-HttpPipelinePrepend <SendAsyncStep[]>] [-NoWait] [-PassThru] [-Proxy <Uri>] [-ProxyCredential <PSCredential>]
[-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm]

    [<CommonParameters>]

DESCRIPTION

Deletes a FHIR Service.

PARAMETERS

-Name <String>

The name of FHIR Service resource.

Required?   true

Position?   named

Default value

Accept pipeline input?   false

Accept wildcard characters? false

-ResourceGroupName <String>

The name of the resource group that contains the service instance.

Required?   true

Position?   named

Default value

Accept pipeline input?   false

Accept wildcard characters? false

-SubscriptionId <String>

The subscription identifier.

Required?   false

Position?   named

Default value

Accept pipeline input?   false

Accept wildcard characters? false

-WorkspaceName <String>

    The name of workspace resource.

    Required?   true

    Position?   named

    Default value

    Accept pipeline input?   false

    Accept wildcard characters? false

-InputObject <IHealthcareApisIdentity>

    Identity Parameter

    To construct, see NOTES section for INPUTOBJECT properties and create a hash table.

    Required?   true

    Position?   named

    Default value

    Accept pipeline input?   true (ByValue)

    Accept wildcard characters? false

-DefaultProfile <PSObject>

    The DefaultProfile parameter is not functional.

    Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

    Required?   false

    Position?   named

    Default value

    Accept pipeline input?   false

    Accept wildcard characters? false

-AsJob [<SwitchParameter>]

    Run the command as a job

    Required?   false

Position?   named

Default value   False

Accept pipeline input?   false

Accept wildcard characters? false

-Break [<SwitchParameter>]

   Wait for .NET debugger to attach

   Required?   false

   Position?   named

   Default value   False

   Accept pipeline input?   false

   Accept wildcard characters? false

-HttpPipelineAppend <SendAsyncStep[]>

   SendAsync Pipeline Steps to be appended to the front of the pipeline

   Required?   false

   Position?   named

   Default value

   Accept pipeline input?   false

   Accept wildcard characters? false

-HttpPipelinePrepend <SendAsyncStep[]>

   SendAsync Pipeline Steps to be prepended to the front of the pipeline

   Required?   false

   Position?   named

   Default value

   Accept pipeline input?   false

   Accept wildcard characters? false

-NoWait [<SwitchParameter>]

Run the command asynchronously

    Required?   false

    Position?   named

    Default value   False

    Accept pipeline input?   false

    Accept wildcard characters? false

-PassThru [<SwitchParameter>]

    Returns true when the command succeeds

    Required?   false

    Position?   named

    Default value   False

    Accept pipeline input?   false

    Accept wildcard characters? false

-Proxy <Uri>

    The URI for the proxy server to use

    Required?   false

    Position?   named

    Default value

    Accept pipeline input?   false

    Accept wildcard characters? false

-ProxyCredential <PSCredential>

    Credentials for a proxy server to use for the remote call

    Required?   false

    Position?   named

    Default value

    Accept pipeline input?   false

Accept wildcard characters? false

-ProxyUseDefaultCredentials [<SwitchParameter>]

   Use the default credentials for the proxy

   Required?   false

   Position?   named

   Default value   False

   Accept pipeline input?   false

   Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

   Required?   false

   Position?   named

   Default value

   Accept pipeline input?   false

   Accept wildcard characters? false

-Confirm [<SwitchParameter>]

   Required?   false

   Position?   named

   Default value

   Accept pipeline input?   false

   Accept wildcard characters? false

<CommonParameters>

   This cmdlet supports the common parameters: Verbose, Debug,

   ErrorAction, ErrorVariable, WarningAction, WarningVariable,

   OutBuffer, PipelineVariable, and OutVariable. For more information, see

   about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

INPUTS

Microsoft.Azure.PowerShell.Cmdlets.HealthcareApis.Models.IHealthcareApisIdentity

OUTPUTS

System.Boolean

NOTES

COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

about_Hash_Tables.

INPUTOBJECT <IHealthcareApisIdentity>: Identity Parameter

[DicomServiceName <String>]: The name of DICOM Service resource.

[FhirDestinationName <String>]: The name of IoT Connector FHIR destination resource.

[FhirServiceName <String>]: The name of FHIR Service resource.

[GroupName <String>]: The name of the private link resource group.

[Id <String>]: Resource identity path

[IotConnectorName <String>]: The name of IoT Connector resource.

[LocationName <String>]: The location of the operation.

[OperationResultId <String>]: The ID of the operation result to get.

[PrivateEndpointConnectionName <String>]: The name of the private endpoint connection associated with the Azure resource

[ResourceGroupName <String>]: The name of the resource group that contains the service instance.

[ResourceName <String>]: The name of the service instance.

[SubscriptionId <String>]: The subscription identifier.

[WorkspaceName <String>]: The name of workspace resource.

-------------------------- EXAMPLE 1 --------------------------

PS   C:\>Remove-AzHealthcareFhirService   -Name   azpsfhirservice   -ResourceGroupName   azps_test_group
-WorkspaceName azpshcws

-------------------------- EXAMPLE 2 --------------------------

PS C:\>Get-AzHealthcareFhirService -Name azpsfhirservice -ResourceGroupName azps_test_group -WorkspaceName
azpshcws | Remove-AzHealthcareFhirService

RELATED LINKS

https://learn.microsoft.com/powershell/module/az.healthcareapis/remove-azhealthcarefhirservice