



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Remove-Event'

PS C:\Users\wahid> Get-Help Remove-Event

NAME

Remove-Event

SYNOPSIS

Deletes events from the event queue.

SYNTAX

Remove-Event [-EventIdentifier] <System.Int32> [-Confirm] [-WhatIf]

[<CommonParameters>]

Remove-Event [-SourceIdentifier] <System.String> [-Confirm] [-WhatIf]

[<CommonParameters>]

DESCRIPTION

The `Remove-Event` cmdlet deletes events from the event queue in the current session.

This cmdlet deletes only the events currently in the queue. To cancel event registrations or unsubscribe, use the `Unregister-Event` cmdlet.

PARAMETERS

`-EventIdentifier <System.Int32>`

Specifies the event identifier for which the cmdlet deletes. An EventIdentifier or SourceIdentifier parameter is required in every command.

`-SourceIdentifier <System.String>`

Specifies the source identifier for which this cmdlet deletes events from. Wildcards are not permitted. An EventIdentifier or SourceIdentifier parameter is required in every command.

`-Confirm <System.Management.Automation.SwitchParameter>`

Prompts you for confirmation before running the cmdlet.

`-WhatIf <System.Management.Automation.SwitchParameter>`

Shows what would happen if the cmdlet runs. The cmdlet is not run.

`<CommonParameters>`

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Remove an event by source identifier -----

```
PS C:\> Remove-Event -SourceIdentifier "ProcessStarted"
```

This command deletes events with a source identifier of Process Started from the event queue.

----- Example 2: Remove an event by event identifier -----

```
PS C:\> Remove-Event -EventIdentifier 30
```

This command deletes the event with an event ID of 30 from the event queue.

----- Example 3: Remove all events -----

```
PS C:\> Get-Event | Remove-Event
```

This command deletes all events from the event queue.

REMARKS

To see the examples, type: "get-help Remove-Event -examples".

For more information, type: "get-help Remove-Event -detailed".

For technical information, type: "get-help Remove-Event -full".

For online help, type: "get-help Remove-Event -online"