



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Remove-FileShare'

PS C:\Users\wahid> Get-Help Remove-FileShare

NAME

Remove-FileShare

SYNOPSIS

Removes a file share.

SYNTAX

```
Remove-FileShare [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-FileServer  
<CimInstance>] -Name <String[]> [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]  
[<CommonParameters>]
```

```
Remove-FileShare [-AsJob] [-CimSession <CimSession[]>] [-Confirm] -InputObject  
<CimInstance[]> [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]  
[<CommonParameters>]
```

```
Remove-FileShare [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-PassThru]  
[-ThrottleLimit <Int32>] -UniqueId <String[]> [-WhatIf] [<CommonParameters>]
```

DESCRIPTION

The Remove-FileShare cmdlet removes the specified file sharing access point.

This operation does not delete data.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or [Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>)cmdlet. The default is the current session on the local computer.

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-FileServer <CimInstance>

Specifies a file server.

-InputObject <CimInstance[]>

Specifies the input object that is used in a pipeline command.

-Name <String[]>

Specifies the name of the file share to remove.

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

`-Uniqueid <String[]>`

Specifies the unique ID of the file share to remove.

`-WhatIf [<SwitchParameter>]`

Shows what would happen if the cmdlet runs. The cmdlet is not run.

`<CommonParameters>`

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<https://go.microsoft.com/fwlink/?LinkID=113216>).

----- Example 1: Remove a file share -----

```
PS C:\>Remove-FileShare -Name "Sales"
```

This command removes the file share named Sales so that it is not accessible over the network.

REMARKS

To see the examples, type: "get-help Remove-FileShare -examples".

For more information, type: "get-help Remove-FileShare -detailed".

For technical information, type: "get-help Remove-FileShare -full".

For online help, type: "get-help Remove-FileShare -online"