



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Remove-NetIPsecRule'

PS C:\Users\wahid> Get-Help Remove-NetIPsecRule

NAME

Remove-NetIPsecRule

SYNOPSIS

Defines security requirements for network connections that match the specified criteria.

SYNTAX

```
Remove-NetIPsecRule [-All] [-AsJob] [-CimSession <CimSession[]>] [-Confirm]
[-GPOSession <String>] [-PassThru] [-PolicyStore <String>] [-ThrottleLimit
<Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]
```

```
Remove-NetIPsecRule [-AllowSetKey <Boolean[]>] [-AllowWatchKey <Boolean[]>]
[-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-Description <String[]>]
[-DisplayGroup <String[]>] [-Enabled {True | False}] [-EncryptedTunnelBypass
<Boolean[]>] [-ForwardPathLifetime <UInt32[]>] [-GPOSession <String>] [-Group
<String[]>] [-InboundSecurity {None | Request | Require}] [-KeyModule {Default
| IKEv1 | AuthIP | IKEv2}] [-Machine <String[]>] [-Mode {None | Tunnel |
Transport}] [-OutboundSecurity {None | Request | Require}] [-PassThru]
[-Phase1AuthSet <String[]>] [-Phase2AuthSet <String[]>] [-PolicyStore
```

<String>] [-PolicyStoreSource <String[]>] [-PolicyStoreSourceType {None | Local | GroupPolicy | Dynamic | Generated | Hardcoded}] [-PrimaryStatus {Unknown | OK | Inactive | Error}] [-QuickModeCryptoSet <String[]>] [-RemoteTunnelHostname <String[]>] [-RequireAuthorization <Boolean[]>] [-Status <String[]>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-User <String[]>] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetFirewallAddressFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetFirewallInterfaceFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetFirewallInterfaceTypeFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetFirewallPortFilter <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetFirewallProfile <CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetIPsecPhase1AuthSet <CimInstance>

[-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru]
[-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf]
[<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetIPsecPhase2AuthSet <CimInstance>
[-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru]
[-PolicyStore <String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf]
[<CommonParameters>]

Remove-NetIPsecRule [-AsJob] -AssociatedNetIPsecQuickModeCryptoSet
<CimInstance> [-CimSession <CimSession[]>] [-Confirm] [-GPOSession <String>]
[-PassThru] [-PolicyStore <String>] [-ThrottleLimit <Int32>]
[-TracePolicyStore] [-WhatIf] [<CommonParameters>]

Remove-NetIPsecRule [-AsJob] [-CimSession <CimSession[]>] [-Confirm]
-DisplayName <String[]> [-GPOSession <String>] [-PassThru] [-PolicyStore
<String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf]
[<CommonParameters>]

Remove-NetIPsecRule [-IPsecRuleName] <String[]> [-AsJob] [-CimSession
<CimSession[]>] [-Confirm] [-GPOSession <String>] [-PassThru] [-PolicyStore
<String>] [-ThrottleLimit <Int32>] [-TracePolicyStore] [-WhatIf]
[<CommonParameters>]

Remove-NetIPsecRule [-AsJob] [-CimSession <CimSession[]>] [-Confirm]
-InputObject <CimInstance[]> [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]

DESCRIPTION

The Remove-NetIPsecRule cmdlet permanently deletes one or more IPsec rules from the specified policy store.

This cmdlet gets one or more IPsec rules to be deleted with the IPsecRuleName parameter (default), the DisplayName parameter, rule properties, or by associated filters or objects. The resulting queried rule is removed from the computer.

This cmdlet permanently removes a previously enabled IPsec rule to be inactive within the computer or a group policy organizational unit. This cmdlet differs from the Disable-NetIPsecRule cmdlet that disables a previously enabled IPsec rule to be inactive within the computer or a group policy organizational unit. A disabled main mode rule will not actively modify computer behavior, but it still exists on the computer or in a Group Policy Object (GPO) so it can be re-enabled.

PARAMETERS

-All [<SwitchParameter>]

Indicates that all of the IPsec rules within the specified policy store are removed.

-AllowSetKey <Boolean[]>

Indicates that matching IPsec rules of the indicated value are removed.

This parameter specifies that the IPsec rule allows trusted intermediaries to override keying material. If this parameter is set to True, then the trusted intermediaries are allowed to manipulate the cryptographic keying material used with an IPsec security association (SA). It is possible that when this parameter is True at both ends, the computer will perform arbitration through SA negotiation so that one end sets the key while the other end watches the key. See the AllowWatchKey parameter for more information. The default value is False. This parameter is only supported on Windows Server 2012.

-AllowWatchKey <Boolean[]>

Indicates that matching IPsec rules of the indicated value are removed.

This parameter specifies that the IPsec rule allows trusted intermediaries to provide notification of changes in keying material. If this parameter is set to True, then the trusted intermediaries are allowed to retrieve the cryptographic keying material associated with an IPsec security association (SA), and to subscribe for notification of changes. The default value is False. This parameter is only supported on Windows Server 2012.

`-AsJob [<SwitchParameter>]`

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

`-AssociatedNetFirewallAddressFilter <CimInstance>`

Gets only the IPsec rules that are associated with the given address filter to be removed. A `NetFirewallAddressFilter` object represents the address conditions associated with a rule. See the `Get-NetFirewallAddressFilter` cmdlet for more information.

`-AssociatedNetFirewallInterfaceFilter <CimInstance>`

Gets the IPsec rules that are associated with the given interface filter to be removed. A `NetFirewallInterfaceFilter` object represents the interface conditions associated with a rule. See the `Get-NetFirewallInterfaceFilter` cmdlet for more information.

`-AssociatedNetFirewallInterfaceTypeFilter <CimInstance>`

Gets the IPsec rules that are associated with the given interface type filter to be removed. A `NetFirewallInterfaceTypeFilter` object represents the interface conditions associated with a rule. See the `Get-NetFirewallInterfaceTypeFilter` cmdlet for more information.

`-AssociatedNetFirewallPortFilter <CimInstance>`

Gets the IPsec rules that are associated with the given port filter to be removed. A `NetFirewallPortFilter` object represents the port conditions

associated with a rule. See the `Get-NetFirewallPortFilter` cmdlet for more information.

`-AssociatedNetFirewallProfile <CimInstance>`

Gets the IPsec rules that are associated with the given firewall profile type to be removed. A `NetFirewallProfile` object represents the profile conditions associated with a rule. See the `Get-NetFirewallProfile` cmdlet for more information.

`-AssociatedNetIPsecPhase1AuthSet <CimInstance>`

Gets the IPsec rules that are associated with the given phase 1 authentication set to be removed. A `NetIPsecPhase1AuthSet` object represents the phase 1 authorization set conditions associated with an IPsec or main mode rule. This parameter sets the methods for main mode negotiation by describing the proposals for computer authentication. See the `Get-NetIPsecPhase1AuthSet` cmdlet for more information. Alternatively, the `Phase1AuthSet` parameter can be used for the same purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the `IPsecRuleName` parameter.

`-AssociatedNetIPsecPhase2AuthSet <CimInstance>`

Gets the IPsec rules that are associated, via the pipeline, with the input phase 2 authentication set to be removed. A `NetIPsecPhase1AuthSet` object represents the phase 2 authorization set conditions associated with a rule. See the `Get-NetIPsecPhase2AuthSet` cmdlet for more information. Alternatively, the `Phase2AuthSet` parameter can be used for the same purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the `IPsecRuleName` parameter.

`-AssociatedNetIPsecQuickModeCryptoSet <CimInstance>`

Gets the IPsec rules that are associated, via the pipeline, with the input quick mode cryptographic set to be removed. A `NetIPsecQuickModeCryptoSet` object represents a quick mode cryptographic set that contains

cryptographic proposals. This parameter specifies parameters for the quick mode negotiation as well as dictating the cryptographic proposals that should be proposed during the exchange. This is only associated with IPsec rules. See the `Get-NetIPsecQuickModeCryptoSet` cmdlet for more information.

Alternatively, the `QuickModeCryptoSet` parameter can be used for the same purpose, but does not allow the cryptographic set to be piped into the cmdlet and the set must be specified with the `IPsecRuleName` parameter.

`-CimSession <CimSession[]>`

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a `New-CimSession` (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

`[Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet.`

The default is the current session on the local computer.

`-Confirm [<SwitchParameter>]`

Prompts you for confirmation before running the cmdlet.

`-Description <String[]>`

Specifies that matching IPsec rules of the indicated description are removed. Wildcard characters are accepted. This parameter provides information about the IPsec rule. This parameter specifies a localized, user-facing description of the object.

`-DisplayGroup <String[]>`

Specifies that only matching firewall rules of the indicated group association are removed. Wildcard characters are accepted. The `Group` parameter specifies the source string for this parameter. If the value for this parameter is a localizable string, then the `Group` parameter contains an indirect string. Rule groups can be used to organize rules by influence and allows batch rule modifications. Using the `Set-NetIPsecRule` cmdlet, if the group name is specified for a set of rules or sets, then all of the rules or sets in that group receive the same set of modifications. It is

good practice to specify the Group parameter value with a universal and world-ready indirect @FirewallAPI name. This parameter cannot be specified upon object creation using the New-NetIPsecRule cmdlet, but can be modified using dot-notation and the Set-NetIPsecRule cmdlet.

-DisplayName <String[]>

Specifies that only matching IPsec rules of the indicated display name are removed. Wildcard characters are accepted. Specifies the localized, user-facing name of the IPsec rule being created. When creating a rule this parameter is required. This parameter value is locale-dependent. If the object is not modified, this parameter value may change in certain circumstances. When writing scripts in multi-lingual environments, the IPsecRuleName parameter should be used instead, where the default value is a randomly assigned value. This parameter cannot be set to All.

-Enabled <Enabled[]>

Specifies that matching IPsec rules of the indicated state are enabled. This parameter specifies that the rule object is administratively enabled or administratively disabled. The acceptable values for this parameter are:

- True: Specifies the rule is currently enabled.

- False: Specifies the rule is currently disabled.

A disabled rule will not actively modify computer behavior, but the management construct still exists on the computer so it can be re-enabled.

-EncryptedTunnelBypass <Boolean[]>

Indicates that matching IPsec rules of the specified value are removed. This parameter specifies the encapsulation state for network traffic sent to a tunnel end point that is already IPsec protected. If this parameter is set to True, then the network traffic sent to a tunnel end point that is already IPsec protected does not have to be encapsulated again. This

option can improve network performance in the case where network traffic that is already end-to-end protected by other IPsec rules. The default value is False. This parameter is only supported on firstref_server_7 and Windows Server 2012.

-ForwardPathLifetime <UInt32[]>

Specifies that matching IPsec rules of the specified path lifetime value are removed. This parameter specifies the session key lifetime for an IPsec rule, in minutes. The acceptable values for this parameter are: 78 through 172799. The default value is 0 minutes. When managing a GPO, the default setting is NotConfigured. This parameter is only supported on Windows Server 2012.

-GPOSession <String>

Specifies the network GPO from which to retrieve the rules to be removed. This parameter is used in the same way as the PolicyStore parameter. When modifying GPOs in Windows PowerShell, each change to a GPO requires the entire GPO to be loaded, modified, and saved back. On a busy Domain Controller (DC), this can be a slow and resource-heavy operation. A GPO Session loads a domain GPO onto the local computer and makes all changes in a batch, before saving it back. This reduces the load on the DC and speeds up the Windows PowerShell cmdlets. To load a GPO Session, use the Open-NetGPO cmdlet. To save a GPO Session, use the Save-NetGPO cmdlet.

-Group <String[]>

Specifies that only matching IPsec rules of the indicated group association are removed. Wildcard characters are accepted. This parameter specifies the source string for the DisplayGroup parameter. If the DisplayGroup parameter value is a localizable string, then this parameter contains an indirect string. Rule groups can be used to organize rules by influence and allows batch rule modifications. Using the Set-NetIPsecRule cmdlets, if the group name is specified for a set of rules or sets, then all of the rules or sets in that group receive the same set of

modifications. It is good practice to specify this parameter value with a universal and world-ready indirect @FirewallAPI name. The DisplayGroup parameter cannot be specified upon object creation using the New-NetIPsecRule cmdlet, but can be modified using dot-notation and the Set-NetIPsecRule cmdlet.

`-IPsecRuleName <String[]>`

Specifies that only matching IPsec rules of the indicated name are removed. Wildcard characters are accepted. This parameter acts just like a file name, in that only one rule with a given name may exist in a policy store at a time. During group policy processing and policy merge, rules that have the same name but come from multiple stores being merged, will overwrite one another so that only one exists. This overwriting behavior is desirable if the rules serve the same purpose. For instance, all of the firewall rules have specific names, so if an administrator can copy these rules to a GPO, and the rules will override the local versions on a local computer. GPOs can have precedence. So if an administrator has a different or more specific rule with the same name in a higher-precedence GPO, then it overrides other rules that exist. The default value is a randomly assigned value. When the defaults for main mode encryption need to be overridden, specify the customized parameters and set this parameter value, making this parameter the new default setting for encryption.

`-InboundSecurity <SecurityPolicy[]>`

Specifies that matching IPsec rules of the indicated security policy are removed. This parameter determines the degree of enforcement for security on inbound traffic. The acceptable values for this parameter are:

- None: No authentication is requested or required for connections that match the rule. It specifies that the local computer does not attempt authentication for any network connections that match this rule. This option is typically used to grant IPsec exemptions for network connections that do not need to be protected by IPsec, but would otherwise match other

rules that could cause the connection to be dropped. - Request: Authentication is requested for connections that match the rule. The local computer attempts to authenticate any inbound network connections that match this rule, but allows the connection if the authentication attempt is not successful. - Require: Authentication is required for connections that match the rule. If the authentication is not successful, then the inbound network traffic is discarded.

The default value is None. When the OutboundSecurity parameter is also specified, the following configurations are valid: InboundSecurity \ OutboundSecurity = None\None, Request\None, Request\Request, Require\Request, or Require\Require.

-InputObject <CimInstance[]>

Specifies the input object that is used in a pipeline command.

-KeyModule <KeyModule[]>

Specifies that matching IPsec rules of the indicated key module are removed. This parameter specifies which keying modules to negotiate. The acceptable values for this parameter are: Default, AuthIP, IKEv1, or IKEv2.

- Default: Equivalent to both IKEv1 and AuthIP. Required in order for the rule to be applied to computers running Windows versions prior to nextref_server_7. ---- There are authorization and cryptographic methods that are only compatible with certain keying modules. This is a very advanced setting intended only for specific interoperability scenarios. Overriding this parameter value may result in traffic being sent in plain-text if the authorization and cryptographic settings are not supported by the keying modules there. - AuthIP: Supported with phase 2 authentication.

- IKEv1: Supported with pre-shared key (PSK), Certificates, and Kerberos.

- IKEv2: Not supported with Kerberos, PSK, or NTLM.

Windows versions prior to Windows Server 2012 only support the Default configuration.

-Machine <String[]>

Specifies that matching IPsec rules of the indicated computer accounts are removed. This parameter specifies that only network packets that are authenticated as incoming from or outgoing to a computer identified in the list of computer accounts (SID) match this rule. This parameter value is specified as an SDDL string.

-Mode <IPsecMode[]>

Specifies that matching IPsec rules of the indicated mode are removed. This parameter specifies the type of IPsec mode connection that the IPsec rule defines. The acceptable values for this parameter are: None, Transport, or Tunnel. The default value is Transport.

-OutboundSecurity <SecurityPolicy[]>

Specifies that matching IPsec rules of the indicated security policy are removed. This parameter determines the degree of enforcement for security on outbound traffic. The acceptable values for this parameter are:

- None: No authentication is requested or required for connections that match the rule. It specifies that the local computer does not attempt authentication for any network connections that match this rule. This option is typically used to grant IPsec exemptions for network connections that do not need to be protected by IPsec, but would otherwise match other rules that could cause the connection to be dropped. - Request: Authentication is requested for connections that match the rule. The local computer attempts to authenticate any outbound network connections that match this rule, but allows the connection if the authentication attempt fails. - Require: Authentication is required for connections that match

the rule. If the authentication is not successful, then the outbound network traffic is discarded. The default value is None. When the InboundSecurity parameter is also specified, the following configurations are valid: InboundSecurity / OutboundSecurity = None\None, Request\None, Request\Request, Require\Request, or Require\Require.

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

-Phase1AuthSet <String[]>

Gets the IPsec rules that are associated with the given phase 1 authentication set to be removed. A NetIPsecPhase1AuthSet object represents the phase 1 authentication set conditions associated with an IPsec or main mode rule. This parameter sets the methods for main mode negotiation by describing the proposals for computer authentication. See the Get-NetIPsecPhase1AuthSet cmdlet for more information. Alternatively, the Phase2AuthSet parameter can be used for the same purpose, but does not allow the authentication set to be piped into the cmdlet and the set must be specified with the IPsecRuleName parameter. When specifying authentication sets, the IPsecRuleName parameter value of the authentication set must be used. The object cannot be directly passed to this cmdlet.

-Phase2AuthSet <String[]>

Gets the IPsec rules that are associated with the given phase 2 authentication set to be removed. A NetIPsecPhase2AuthSet object represents the phase 2 authorization set conditions associated with an IPsec or main mode rule. This parameter sets the methods for main mode negotiation by describing the proposals for computer authentication. See the Get-NetIPsecPhase2AuthSet cmdlet for more information. Alternatively, the Phase1AuthSet parameter can be used for the same purpose, but does not allow the authentication set to be piped into the cmdlet and the set must

be specified with the IPsecRuleName parameter. When specifying authentication sets, the IPsecRuleName parameter value of the authentication set must be used. The object cannot be directly passed to this cmdlet.

-PolicyStore <String>

Specifies the policy store from which to retrieve the rules to be removed.

A policy store is a container for firewall and IPsec policy. The acceptable values for this parameter are:

- PersistentStore: Sometimes called static rules, this store contains the persistent policy for the local computer. This policy is not from GPOs, and has been created manually or programmatically (during application installation) on the computer. Rules created in this store are attached to the ActiveStore and activated on the computer immediately. - ActiveStore:

This store contains the currently active policy, which is the sum of all policy stores that apply to the computer. This is the resultant set of policy (RSOP) for the local computer (the sum of all GPOs that apply to the computer), and the local stores (the PersistentStore, the static Windows service hardening (WSH), and the configurable WSH). ---- GPOs are also policy stores. Computer GPOs can be specified as follows. -----

`-PolicyStore hostname`.

---- Active Directory GPOs can be specified as follows.

----- `-PolicyStore

domain.fqdn.com\GPO_Friendly_Namedomain.fqdn.comGPO_Friendly_Name`.

----- Such as the following.

----- `-PolicyStore localhost`

----- `-PolicyStore corp.contoso.com\FirewallPolicy`

---- Active Directory GPOs can be created using the New-GPO cmdlet or the Group Policy Management Console. - RSOP: This read-only store contains the sum of all GPOs applied to the local computer.

- SystemDefaults: This read-only store contains the default state of firewall rules that ship with Windows Server 2012.

- StaticServiceStore: This read-only store contains all the service restrictions that ship with Windows Server 2012.

Optional and product-dependent features are considered part of Windows Server 2012 for the purposes of WFAS. - ConfigurableServiceStore: This read-write store contains all the service restrictions that are added for third-party services. In addition, network isolation rules that are created for Windows Store application containers will appear in this policy store. The default value is PersistentStore. The Set-NetIPsecRule cmdlet cannot be used to add an object to a policy store. An object can only be added to a policy store at creation time with the Copy-NetIPsecRule cmdlet or with the New-NetIPsecRule cmdlet.

-PolicyStoreSource <String[]>

Specifies that IPsec rules matching the indicated policy store source are removed. This parameter contains a path to the policy store where the rule originated if the object is retrieved from the ActiveStore with the TracePolicyStoreSource option set. This parameter value is automatically generated and should not be modified. The monitoring output from this parameter is not completely compatible with the PolicyStore parameter. This parameter value cannot always be passed into the PolicyStore parameter. Domain GPOs are one example in which this parameter contains only the GPO name, not the domain name.

-PolicyStoreSourceType <PolicyStoreType[]>

Specifies that IPsec rules that match the indicated policy store source type are removed. This parameter describes the type of policy store where the rule originated if the object is retrieved from the ActiveStore with the TracePolicyStoreSource option set. This parameter value is automatically generated and should not be modified. The acceptable values for this parameter are:

- Local: The object originates from the local store.
- GroupPolicy: The object originates from a GPO.
- Dynamic: The object originates from the local runtime state.

This policy store name is not valid for use in the cmdlets, but may appear when monitoring active policy. - Generated: The object was generated automatically. This policy store name is not valid for use in the cmdlets, but may appear when monitoring active policy. - Hardcoded: The object was hard-coded. This policy store name is not valid for use in the cmdlets, but may appear when monitoring active policy.

-PrimaryStatus <PrimaryStatus[]>

Specifies that IPsec rules that match the indicated primary status are removed. This parameter specifies the overall status of the rule. - OK: Specifies that the rule will work as specified.

- Degraded: Specifies that one or more parts of the rule will not be enforced.
- Error: Specifies that the computer is unable to use the rule at all.

See the Status and StatusCode fields of the object for more detailed status information.

-QuickModeCryptoSet <String[]>

Specifies that matching IPsec rules of the specified quick mode cryptographic set are removed. This parameter specifies the quick mode cryptographic set to be associated with the IPsec rule. A NetIPsecMainModeCryptoSet object represents quick mode cryptographic conditions associated with an IPsec rule. This parameter sets the methods for quick mode negotiation by describing the proposals for encryption. See the New-NetIPsecQuickModeCryptoSet cmdlet for more information. Alternatively, the AssociatedNetIPsecQuickModeCryptoSet parameter can be used for the same purpose, but is used to pipe the input set into the rule. When specifying authentication sets, the IPsecRuleName parameter value of the authentication set must be used. The object cannot be directly passed to this cmdlet.

-RemoteTunnelHostname <String[]>

Specifies that matching IPsec rules of the specified second end point tunnel host name are removed. Specifies a fully qualified DNS name that resolves to a list of remote tunnel end points. This parameter is only supported on Windows Server 2012. This parameter can only be used with multiple remote tunnel end points. Specifying this parameter prevents a non-asymmetric tunnel mode IPsec rule from being created. Rule creation will fail when a single remote tunnel end point and this parameter are specified, or when remote tunnel end point is Any and this parameter is specified.

-RequireAuthorization <Boolean[]>

Indicates that matching IPsec rules of the specified value are removed. Specifies the given value for an IPsec rule. If this parameter is set to True, then enforcement of authorization is allowed for end points. This parameter is only supported on nextref_server_7 and Windows Server 2012.

-Status <String[]>

Specifies that IPsec rules that match the indicated status are removed.

This parameter describes the status message for the specified status code value. The status code is a numerical value that indicates any syntax, parsing, or run-time errors in the rule or set. This parameter value should not be modified.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

-TracePolicyStore [<SwitchParameter>]

Specifies that the name of the source GPO is queried and set to the PolicyStoreSource parameter value.

-User <String[]>

Specifies that matching IPsec rules of the indicated user accounts are removed. This parameter specifies that only network packets that are authenticated as incoming from or outgoing to a user identified in the list of user accounts match this rule. This parameter value is specified as an SDDL string.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- EXAMPLE 1 -----

```
PS C:\>Remove-NetIPsecRule
```

This example removes all of the static local policies.

----- EXAMPLE 2 -----

```
PS C:\>Remove-NetIPsecRule -DisplayName " Transport Mode - CorpNet IPv4 -  
AuthIP"
```

This example deletes an IPsec rule based on the localized name.

----- EXAMPLE 3 -----

```
PS C:\>Remove-NetIPsecRule -Enabled False -PolicyStore contoso.com\gpo_name
```

This example removes all of the IPsec rules that are currently disabled on a GPO.

----- EXAMPLE 4 -----

```
PS C:\>$nfProfile = Get-NetFirewallProfile -Profile Public
```

```
PS C:\>Remove-NetIPsecRule -InputObject $nfProfile
```

This example removes all of the IPsec rules associated with the public profile.

REMARKS

To see the examples, type: "get-help Remove-NetIPsecRule -examples".

For more information, type: "get-help Remove-NetIPsecRule -detailed".

For technical information, type: "get-help Remove-NetIPsecRule -full".

For online help, type: "get-help Remove-NetIPsecRule -online"