MyWebUniversity *







Full credit is given to the above companies including the OS that this TDF file was generated!

PowerShell Get-Help on command 'Reset-DtcLog'

PS C:\Users\wahid> Get-Help Reset-DtcLog

NAME

Reset-DtcLog

SYNOPSIS

Resets the log file of a DTC instance.

SYNTAX

Reset-DtcLog [-AsJob] [-CimSession < CimSession[]>] [-Confirm] [-DtcName < String>] [-ThrottleLimit < Int32>] [-WhatIf] [< CommonParameters>]

DESCRIPTION

The Reset-DtcLog cmdlet resets the log file of a Distributed Transaction

Coordinator (DTC) instance. You can use the DtcName parameter to specify a DTC instance. This cmdlet also recreates the transactions log with the existing settings and restarts the DTC instance.

PARAMETERS

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

The cmdlet immediately returns an object that represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the `*-Job` cmdlets. To get the job results, use the Receive-Job (https://go.microsoft.com/fwlink/?LinkID=113372)cmdlet.

For more information about Windows PowerShell background jobs, see about_Jobs (https://go.microsoft.com/fwlink/?LinkID=113251).

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession (https://go.microsoft.com/fwlink/p/?LinkId=227967) or [Get-CimSession](https://go.microsoft.com/fwlink/p/?LinkId=227966)cmdlet. The default is the current session on the local computer.

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-DtcName <String>

Specifies a DTC instance. The cmdlet resets the log file for this instance. If you do not specify this parameter, or if you specify a value of Local, this cmdlet resets the log file for the local DTC instance.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShellr calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet,

not to the session or to the computer.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug,
ErrorAction, ErrorVariable, WarningAction, WarningVariable,
OutBuffer, PipelineVariable, and OutVariable. For more information, see
about_CommonParameters (https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Reset a DTC log ------

PS C:\> Reset-DtcLog -DtcName "Local" -Confirm:\$False -WhatIf:\$False

This command resets the log file for the Local DTC instance.

REMARKS

To see the examples, type: "get-help Reset-DtcLog -examples".

For more information, type: "get-help Reset-DtcLog -detailed".

For technical information, type: "get-help Reset-DtcLog -full".

For online help, type: "get-help Reset-DtcLog -online"