



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Set-IscsiChapSecret'

PS C:\Users\wahid> Get-Help Set-IscsiChapSecret

NAME

Set-IscsiChapSecret

SYNOPSIS

Sets a CHAP secret key for use with iSCSI initiator connections.

SYNTAX

```
Set-IscsiChapSecret [-AsJob] [-ChapSecret <String>] [-CimSession  
<CimSession[]>] [-ThrottleLimit <Int32>] [<CommonParameters>]
```

DESCRIPTION

The Set-IscsiChapSecret cmdlet sets a CHAP secret key for use with iSCSI initiator connections.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

The cmdlet immediately returns an object that represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the ``*-Job`` cmdlets. To get the job results, use the `Receive-Job` (<https://go.microsoft.com/fwlink/?LinkID=113372>) cmdlet.

For more information about Windows PowerShell background jobs, see `about_Jobs` (<https://go.microsoft.com/fwlink/?LinkID=113251>).

`-ChapSecret <String>`

Specifies the CHAP secret key for use with the iSCSI initiator connections.

`-CimSession <CimSession[]>`

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a `New-CimSession` (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or `[Get-CimSession]` (<https://go.microsoft.com/fwlink/p/?LinkId=227966>) cmdlet. The default is the current session on the local computer.

`-ThrottleLimit <Int32>`

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of ``0`` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

`<CommonParameters>`

This cmdlet supports the common parameters: `Verbose`, `Debug`, `ErrorAction`, `ErrorVariable`, `WarningAction`, `WarningVariable`, `OutBuffer`, `PipelineVariable`, and `OutVariable`. For more information, see `about_CommonParameters` (<https://go.microsoft.com/fwlink/?LinkID=113216>).

----- Example 1: Set CHAP secret key -----

```
PS C:\> Set-IscsiChapSecret -ChapSecret "12345678912345"
```

This command sets the CHAP secret key to a value.

REMARKS

To see the examples, type: "get-help Set-IscsiChapSecret -examples".

For more information, type: "get-help Set-IscsiChapSecret -detailed".

For technical information, type: "get-help Set-IscsiChapSecret -full".

For online help, type: "get-help Set-IscsiChapSecret -online"