



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Set-NetAdapterSriov'

PS C:\Users\wahid> Get-Help Set-NetAdapterSriov

NAME

Set-NetAdapterSriov

SYNOPSIS

Sets the SR-IOV properties of the network adapter, such as the number of virtual functions, and the number of queue pairs for default and non-default VPorts.

SYNTAX

```
Set-NetAdapterSriov [-Name] <String[]> [-AsJob] [-CimSession <CimSession[]>]
[-Confirm] [-Enabled <Boolean>] [-IncludeHidden] [-NoRestart] [-NumVFs
<UInt32>] [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]
```

```
Set-NetAdapterSriov [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-Enabled
<Boolean>] [-IncludeHidden] -InterfaceDescription <String[]> [-NoRestart]
[-NumVFs <UInt32>] [-PassThru] [-ThrottleLimit <Int32>] [-WhatIf]
[<CommonParameters>]
```

```
Set-NetAdapterSriov [-AsJob] [-CimSession <CimSession[]>] [-Confirm] [-Enabled
<Boolean>] -InputObject <CimInstance[]> [-NoRestart] [-NumVFs <UInt32>]
```

[-PassThru] [-ThrottleLimit <Int32>] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Set-NetAdapterSriov cmdlet sets the Single-Root I/O Virtualization (SR-IOV) properties of the network adapter. The properties include the number of virtual functions, the number of virtual ports (VPorts), and the number of queue pairs for default and non-default VPorts. The enabled state of SR-IOV can also be set with the cmdlet.

The network adapter for these actions can be specified with the adapter name, interface description, or piped as an input object.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete. The cmdlet immediately returns an object that represents the job and then displays the command prompt. You can continue to work in the session while the job completes. To manage the job, use the `*-Job` cmdlets. To get the job results, use the Receive-Job (<https://go.microsoft.com/fwlink/?LinkID=113372>)cmdlet. For more information about Windows PowerShell background jobs, see about_Jobs (<https://go.microsoft.com/fwlink/?LinkID=113251>).

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession (<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or [Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>)cmdlet. The default is the current session on the local computer.

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-Enabled <Boolean>

Indicates whether SR-IOV is enabled on the network adapter. If set to \$True, then SR-IOV is Enabled. If set to \$False, then SR-IOV is Disabled.

-IncludeHidden [<SwitchParameter>]

Indicates that the cmdlet includes both visible and hidden network adapters in the operation. By default only visible network adapters are included. If a wildcard character is used in identifying a network adapter and this parameter has been specified, then the wildcard string is matched against both hidden and visible network adapters.

-InputObject <CimInstance[]>

Specifies the input to this cmdlet. You can use this parameter, or you can pipe the input to this cmdlet.

-InterfaceDescription <String[]>

Specifies an array of network adapter interface descriptions. For a physical network adapter this is typically the name of the vendor of the network adapter followed by a part number and description, such as `Contoso 12345 Gigabit Network Device`.

The network adapter can be selected using the Name parameter, this parameter, or piped in using the InputObject parameter.

-Name <String[]>

Specifies an array of network adapter names.

The network adapter can be selected using this parameter, the InterfaceDescription parameter, or piped in using the InputObject parameter.

-NoRestart [<SwitchParameter>]

Indicates that the cmdlet does not restart the network adapter after completing the operation. Many advanced properties require restarting the network adapter before the new settings take effect.

-NumVFs <UInt32>

Specifies the number of virtual functions that the network adapter exposes for SR-IOV. This is the maximum number of virtual functions that Windows Server 2012 and later allocates on this network adapter.

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By default, this cmdlet does not generate any output.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see `about_CommonParameters` (<https://go.microsoft.com/fwlink/?LinkID=113216>).

Example 1: Set the number of virtual functions on the specified network adapter

```
PS C:\> Set-NetAdapterSriov -Name "Ethernet 2" -NumVFs 31
```

This command sets the number of virtual functions available to 31 on the network adapter named Ethernet 2.

Example 2: Set the number of virtual functions and VPorts on the specified network adapter

```
PS C:\> Set-NetAdapterSriov -Name "Ethernet 2" -NumVFs 31  
-NumQueuePairsForDefaultVPort 2 -NumQueuePairsForNonDefaultVPort 2
```

This command sets the number of virtual functions to 31. This results in 31 virtual functions and 32 virtual machine queues (VMQ), plus 1 used by the physical function. Since the number of queue pair is set to 2 for both default and non-default ports, the total number of queue pairs used is 128.

REMARKS

To see the examples, type: "get-help Set-NetAdapterSriov -examples".

For more information, type: "get-help Set-NetAdapterSriov -detailed".

For technical information, type: "get-help Set-NetAdapterSriov -full".

For online help, type: "get-help Set-NetAdapterSriov -online"