



python



PowerShell

FPDF Library
PDF generator

Full credit is given to the above companies including the OS that this PDF file was generated!

PowerShell Get-Help on command 'Set-SmbShare'

PS C:\Users\wahid> Get-Help Set-SmbShare

NAME

Set-SmbShare

SYNOPSIS

Modifies the properties of the SMB share.

SYNTAX

```
Set-SmbShare [-AsJob] [-CATimeout <UInt32>] [-CachingMode {None | Manual | Documents | Programs | BranchCache | Unknown}] [-CimSession <CimSession[]>] [-CompressData <Boolean>] [-ConcurrentUserLimit <UInt32>] [-ContinuouslyAvailable <Boolean>] [-Description <String>] [-EncryptData <Boolean>] [-FolderEnumerationMode {AccessBased | Unrestricted}] [-Force] [-InputObject <CimInstance[]>] [-LeasingMode <LeasingMode>] [-PassThru] [-SecurityDescriptor <String>] [-ThrottleLimit <Int32>] [-Confirm] [-WhatIf] [<CommonParameters>]
```

```
Set-SmbShare [-Name] <String[]> [[-ScopeName] <String[]>] [-AsJob] [-CATimeout <UInt32>] [-CachingMode {None | Manual | Documents | Programs | BranchCache | Unknown}] [-CimSession <CimSession[]>] [-CompressData <Boolean>] [-ConcurrentUserLimit <UInt32>] [-ContinuouslyAvailable <Boolean>]
```

[-Description <String>] [-EncryptData <Boolean>] [-FolderEnumerationMode {AccessBased | Unrestricted}] [-Force] [-LeasingMode <LeasingMode>] [-PassThru] [-SecurityDescriptor <String>] [-SmbInstance {Default | CSV | SBL | SR}] [-ThrottleLimit <Int32>] [-Confirm] [-WhatIf] [<CommonParameters>]

DESCRIPTION

The Set-SmbShare cmdlet modifies the properties of the Server Message Block (SMB) share.

PARAMETERS

-AsJob [<SwitchParameter>]

Runs the cmdlet as a background job. Use this parameter to run commands that take a long time to complete.

-CATimeout <UInt32>

Specifies the continuous availability time-out of the SMB share.

-CachingMode <CachingMode>

Specifies the caching mode of the offline files for the SMB share. There are five caching modes:

- None. Prevents users from storing documents and programs offline. -

Manual. Allows users to identify the documents and programs that they want

to store offline. - Programs. Automatically stores documents and programs

offline. - Documents. Automatically stores documents offline. -

BranchCache. Enables BranchCache and manual caching of documents on the shared folder.

-CimSession <CimSession[]>

Runs the cmdlet in a remote session or on a remote computer. Enter a computer name or a session object, such as the output of a New-CimSession

(<https://go.microsoft.com/fwlink/p/?LinkId=227967>) or

[Get-CimSession](<https://go.microsoft.com/fwlink/p/?LinkId=227966>)cmdlet.

The default is the current session on the local computer.

-CompressData <Boolean>

Indicates that the shares being enumerated should request compression from clients.

-ConcurrentUserLimit <UInt32>

Specifies the maximum number of concurrently connected users that the SMB share may accommodate. If this parameter is set to zero (0), then the number of users is unlimited. By default, new SMB shares have no limit on the number of concurrent connections.

-ContinuouslyAvailable <Boolean>

Indicates whether the share is continuously available.

-Description <String>

Specifies an optional description of the SMB share. A description of the share can be displayed by running the Get-SmbShare cmdlet. Specify an empty string to clear the current description. The description may not contain more than 256 characters.

-EncryptData <Boolean>

Indicates whether the SMB share is encrypted.

-FolderEnumerationMode <FolderEnumerationMode>

Specifies which files and folders in the new SMB share will be visible to the users. The acceptable values for this parameter are:

- AccessBased. SMB does not the display the files and folders for a share to a user unless that user has rights to access the files and folders. By default, access-based enumeration is disabled for new SMB shares. -

Unrestricted. SMB displays files and folders to a user even when the user does not have permission to access those items.

The default value is Unrestricted.

-Force [<SwitchParameter>]

Forces the command to run without asking for user confirmation.

-InputObject <CimInstance[]>

Specifies the input object that is used in a pipeline command.

-LeasingMode <LeasingMode>

Specifies SMB leasing and oplock behaviors for application compatibility.

The acceptable values for this parameter are:

- `Full:` Use default lease and oplock behaviors from SMB3.

- `Shared:` Grant read-caching lease but not write or handle-caching.

- `None:` No oplocks or leases, behave like SMB1 (not recommended).

> [!IMPORTANT] > We do not recommend disabling oplocks, but may be required in some scenarios. For more information, see SMB1 Product Clearinghouse (<https://techcommunity.microsoft.com/t5/Storage-at-Microsoft/SMB1-Product-Clearinghouse/ba-p/426008>).

-Name <String[]>

Specifies the name of one or more SMB shares.

-PassThru [<SwitchParameter>]

Returns an object representing the item with which you are working. By

default, this cmdlet does not generate any output.

-ScopeName <String[]>

Specifies the scope name of the SMB share. For use with Windows Server failover cluster file server resources.

-SecurityDescriptor <String>

Specifies the security descriptor for the SMB share in string format.

-SmbInstance <SmbInstance>

Specifies the input to this cmdlet. You can use this parameter, or you can pipe the input to this cmdlet.

-ThrottleLimit <Int32>

Specifies the maximum number of concurrent operations that can be established to run the cmdlet. If this parameter is omitted or a value of `0` is entered, then Windows PowerShell calculates an optimum throttle limit for the cmdlet based on the number of CIM cmdlets that are running on the computer. The throttle limit applies only to the current cmdlet, not to the session or to the computer.

-Confirm [<SwitchParameter>]

Prompts you for confirmation before running the cmdlet.

-WhatIf [<SwitchParameter>]

Shows what would happen if the cmdlet runs. The cmdlet is not run.

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see [about_CommonParameters \(https://go.microsoft.com/fwlink/?LinkID=113216\)](https://go.microsoft.com/fwlink/?LinkID=113216).

----- Example 1: Modify properties of an SMB share -----

```
PS C:\>Set-SmbShare -Name "VMFiles" -EncryptData $True
```

Confirm

Are you sure you want to perform this action?

Performing operation 'Modify' on Target 'Contoso-SO,VMFiles'.

[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"):

This command modifies the properties of an SMB share.

Example 2: Modify properties of an SMB share without confirmation

```
PS C:\>Set-SmbShare -Name "VMFiles" -EncryptData $True -Force
```

This command modifies the properties of an SMB share without user confirmation.

REMARKS

To see the examples, type: "get-help Set-SmbShare -examples".

For more information, type: "get-help Set-SmbShare -detailed".

For technical information, type: "get-help Set-SmbShare -full".

For online help, type: "get-help Set-SmbShare -online"