PowerShell Get-Help on command 'Set-WinHomeLocation'

PS C:\Users\wahid> Get-Help Set-WinHomeLocation

NAME

   Set-WinHomeLocation

SYNOPSIS

   Sets the home location setting for the current user account.

SYNTAX

   Set-WinHomeLocation [-GeoId] <Int32> [<CommonParameters>]

DESCRIPTION

   The Set-WinHomeLocation cmdlet sets the value of the user GeoID object. The

   Windows GeoID setting is a user setting that describes the home location of

   the current user account. A home location is the country or region.

   Applications that require the home location of the current user account, such

   as a driver for a television tuner application, can use this setting.

   For a table of GeoIDs, see Table of Geographical Locations

   (https://go.microsoft.com/fwlink/?LinkID=242308).

PARAMETERS

    -GeoId <Int32>

        Specifies a GeoID setting.

    <CommonParameters>

        This cmdlet supports the common parameters: Verbose, Debug,

        ErrorAction, ErrorVariable, WarningAction, WarningVariable,

        OutBuffer, PipelineVariable, and OutVariable. For more information, see

        about_CommonParameters (https:/go.microsoft.com/fwlink/?LinkID=113216).

    --------------- Example 1: Set the home location ---------------

    PS C:\> Set-WinHomeLocation -GeoId 0xF4

    This command sets the home location for the current user account to 0xF4 (hex)

    (United States).

REMARKS

    To see the examples, type: "get-help Set-WinHomeLocation -examples".

    For more information, type: "get-help Set-WinHomeLocation -detailed".

    For technical information, type: "get-help Set-WinHomeLocation -full".

    For online help, type: "get-help Set-WinHomeLocation -online"