



**Full credit is given to all the above companies including the Operating System that this PDF file was generated!**

### ***Windows PowerShell Get-Help on Cmdlet 'Update-AzDataCollectionEndpoint'***

**PS:\>Get-HELP Update-AzDataCollectionEndpoint -Full**

#### **NAME**

Update-AzDataCollectionEndpoint

#### **SYNOPSIS**

Update part of a data collection endpoint.

#### **SYNTAX**

```
Update-AzDataCollectionEndpoint -Name <String> -ResourceGroupName <String> [-SubscriptionId <String>]
[-IdentityType <String>] [-Tag <Hashtable>]
[-UserAssignedIdentity <Hashtable>] [-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>]
[-HttpPipelinePrepend <SendAsyncStep[]>] [-Proxy
<Uri>] [-ProxyCredential <PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

```
Update-AzDataCollectionEndpoint -InputObject <IDataCollectionRuleIdentity> [-IdentityType <String>] [-Tag
<Hashtable>] [-UserAssignedIdentity <Hashtable>]
[-DefaultProfile <PSObject>] [-Break] [-HttpPipelineAppend <SendAsyncStep[]>] [-HttpPipelinePrepend
<SendAsyncStep[]>] [-Proxy <Uri>] [-ProxyCredential
<PSCredential>] [-ProxyUseDefaultCredentials] [-WhatIf] [-Confirm] [<CommonParameters>]
```

## DESCRIPTION

Update part of a data collection endpoint.

## PARAMETERS

### -Name <String>

The name of the data collection endpoint.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -ResourceGroupName <String>

The name of the resource group.

The name is case insensitive.

Required? true

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

### -SubscriptionId <String>

The ID of the target subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-InputObject <IDataCollectionRuleIdentity>

Identity Parameter

Required? true

Position? named

Default value

Accept pipeline input? true (ByValue)

Accept wildcard characters? false

-IdentityType <String>

Type of managed service identity (where both SystemAssigned and UserAssigned types are allowed).

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-Tag <Hashtable>

Resource tags.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

-UserAssignedIdentity <Hashtable>

The set of user assigned identities associated with the resource.

The userAssignedIdentities dictionary keys will be ARM resource ids in the form:

'/subscriptions/{subscriptionId}/resourceGroups/{resourceGroupName}/providers/Microsoft.ManagedIdentity/userAssignedIdentities/{identityName}.

The dictionary values can be empty objects ({} ) in requests.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -DefaultProfile <PSObject>

The DefaultProfile parameter is not functional.

Use the SubscriptionId parameter when available if executing the cmdlet against a different subscription.

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Break [<SwitchParameter>]

Wait for .NET debugger to attach

Required? false

Position? named

Default value False

Accept pipeline input? false

Accept wildcard characters? false

#### -HttpPipelineAppend <SendAsyncStep[]>

SendAsync Pipeline Steps to be appended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -HttpPipelinePrepend <SendAsyncStep[]>

SendAsync Pipeline Steps to be prepended to the front of the pipeline

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -Proxy <Uri>

The URI for the proxy server to use

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyCredential <PSCredential>

Credentials for a proxy server to use for the remote call

Required? false

Position? named

Default value

Accept pipeline input? false

Accept wildcard characters? false

#### -ProxyUseDefaultCredentials [<SwitchParameter>]

Use the default credentials for the proxy

Required? false  
Position? named  
Default value False  
Accept pipeline input? false  
Accept wildcard characters? false

-WhatIf [<SwitchParameter>]

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

-Confirm [<SwitchParameter>]

Required? false  
Position? named  
Default value  
Accept pipeline input? false  
Accept wildcard characters? false

<CommonParameters>

This cmdlet supports the common parameters: Verbose, Debug, ErrorAction, ErrorVariable, WarningAction, WarningVariable, OutBuffer, PipelineVariable, and OutVariable. For more information, see about\_CommonParameters (<https://go.microsoft.com/fwlink/?LinkId=113216>).

## INPUTS

Microsoft.Azure.PowerShell.Cmdlets.Monitor.DataCollection.Models.IDataCollectionRuleIdentity

## OUTPUTS

Microsoft.Azure.PowerShell.Cmdlets.Monitor.DataCollection.Models.IDataCollectionEndpointResource

## NOTES

### COMPLEX PARAMETER PROPERTIES

To create the parameters described below, construct a hash table containing the appropriate properties. For information on hash tables, run Get-Help

`about_Hash_Tables`.

#### INPUTOBJECT <IDataCollectionRuleIdentity>: Identity Parameter

[`AssociationName <String>`]: The name of the association. The name is case insensitive.

[`DataCollectionEndpointName <String>`]: The name of the data collection endpoint. The name is case insensitive.

[`DataCollectionRuleName <String>`]: The name of the data collection rule. The name is case insensitive.

[`Id <String>`]: Resource identity path

[`ResourceGroupName <String>`]: The name of the resource group. The name is case insensitive.

[`ResourceUri <String>`]: The identifier of the resource.

[`SubscriptionId <String>`]: The ID of the target subscription.

#### ----- EXAMPLE 1 -----

```
PS C:\>Update-AzDataCollectionEndpoint -Name myCollectionEndpoint -ResourceGroupName AMCS-TEST -Tag @>{"123"="abc"}
```

## RELATED LINKS

<https://learn.microsoft.com/powershell/module/az.monitor/update-azdatacollectionendpoint>