



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on '_exit.2' command

\$ man _exit.2

_EXIT(2) Linux Programmer's Manual _EXIT(2)

NAME

_exit, _Exit - terminate the calling process

SYNOPSIS

```
#include <unistd.h>

void _exit(int status);

#include <stdlib.h>

void _Exit(int status);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

```
_Exit():

    _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

_exit() terminates the calling process "immediately". Any open file descriptors belonging to the process are closed. Any children of the process are inherited by init(1) (or by the nearest "subreaper" process as defined through the use of the prctl(2) PR_SET_CHILD_SUBREAPER operation). The process's parent is sent a SIGCHLD signal.

The value status & 0xFF is returned to the parent process as the process's exit status, and can be collected by the parent using one of the wait(2) family of calls.

The function _Exit() is equivalent to _exit().

RETURN VALUE

These functions do not return.

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SVr4, 4.3BSD. The function `_Exit()` was introduced by C99.

NOTES

For a discussion on the effects of an exit, the transmission of exit status, zombie processes, signals sent, and so on, see `exit(3)`.

The function `_exit()` is like `exit(3)`, but does not call any functions registered with `atexit(3)` or `on_exit(3)`. Open `stdio(3)` streams are not flushed. On the other hand, `_exit()` does close open file descriptors, and this may cause an unknown delay, waiting for pending output to finish. If the delay is undesired, it may be useful to call functions like `tcflush(3)` before calling `_exit()`. Whether any pending I/O is canceled, and which pending I/O may be canceled upon `_exit()`, is implementation-dependent.

C library/kernel differences

In glibc up to version 2.3, the `_exit()` wrapper function invoked the kernel system call of the same name. Since glibc 2.3, the wrapper function invokes `exit_group(2)`, in order to terminate all of the threads in a process. (The raw `_exit()` system call terminates only the calling thread.)

SEE ALSO

`execve(2)`, `exit_group(2)`, `fork(2)`, `kill(2)`, `wait(2)`, `wait4(2)`, `waitpid(2)`, `atexit(3)`, `exit(3)`, `on_exit(3)`, `termios(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.