

Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'asinl.3' command

\$ man asinl.3

ASIN(3) Linux Programmer's Manual ASIN(3) NAME asin, asinf, asinl - arc sine function **SYNOPSIS** #include <math.h> double asin(double x); float asinf(float x); long double asinl(long double x); Link with -lm. Feature Test Macro Requirements for glibc (see feature_test_macros(7)): asinf(), asinI(): _ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L || /* Since glibc 2.19: */ _DEFAULT_SOURCE || /* Glibc versions <= 2.19: */ _BSD_SOURCE || _SVID_SOURCE **DESCRIPTION** These functions calculate the principal value of the arc sine of x; that is the value whose sine is x. **RETURN VALUE**

Page 1/2

On success, these functions return the principal value of the arc sine

of x in radians; the return value is in the range [-pi/2, pi/2].

If x is a NaN, a NaN is returned.

If x is +0 (-0), +0 (-0) is returned.

returned.

ERRORS

See math_error(7) for information on how to determine whether an error has occurred when calling these functions.

The following errors can occur:

Domain error: x is outside the range [-1, 1]

errno is set to EDOM. An invalid floating-point exception (FE_INVALID) is raised.

ATTRIBUTES

For an explanation of the terms used in this section, see at? tributes(7).

?Interface ? Attribute ? Value ?

?asin(), asinf(), asinl() ? Thread safety ? MT-Safe ?

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning double also conforms to SVr4, 4.3BSD, C89.

SEE ALSO

acos(3), atan(3), atan2(3), casin(3), cos(3), sin(3), tan(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

2017-09-15 ASIN(3)