



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'console.handlers.5' command**

**\$ man console.handlers.5**

console.handlers(5) System Administrator's Manual console.handlers(5)

### NAME

console.handlers - file specifying handlers of console lock and unlock events

### DESCRIPTION

/etc/security/console.handlers determines which programs will be run when an user obtains the console lock at login time, and when the user loses it on log out. It is read by the pam\_console module.

The format is:

handler-filename lock|unlock [flag ...]

Where handler-filename is a name of the executable to be run, lock or unlock specifies on which event it should be run, and flags specify how should pam\_console call it.

Additionally there should be a line which specifies glob patterns of console devices.

The format of this line is: console-name consoledevs regex [regex ...]

Where console-name is a name of the console class - currently ignored - and regexes are regular expression patterns which specify the name of the tty device. Only the first such line is consulted.

## FLAGS

### logfail

The pam\_console module should log error to the system log if the return value of the handler is not zero or if the handler can not be executed.

wait The pam\_console should wait for the handler to exit before continuing.

setuid The handler should be executed with uid/gid of the user which obtained the console lock.

tty The handler will get a tty name as obtained from PAM as a parameter.

user The handler will get an user name as obtained from PAM as a parameter.

Anything else will be added directly as a parameter to the handler executable.

## SEE ALSO

pam\_console(8)

## AUTHOR

Tomas Mraz <tmraz@redhat.com>