



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'containers-registries.conf.d.5' command**

**`$ man containers-registries.conf.d.5`**

CONTAINERS-REGISTRIES.CONF.D(5)File Formats ManuCONTAINERS-REGISTRIES.CONF.D(5)

Valentin Rothberg Mar 2020

### NAME

containers-registries.conf.d - directory for drop-in registries.conf files

### DESCRIPTION

CONTAINERS-REGISTRIES.CONF.D is a system-wide directory for drop-in configuration files in the containers-registries.conf(5) format.

By default, the directory is located at /etc/containers/registries.conf.d.

### CONFIGURATION PRECEDENCE

Once the main configuration at /etc/containers/registries.conf is loaded, the files in /etc/containers/registries.conf.d are loaded in alpha-numerical order. Then the conf files in \$HOME/.config/containers/registries.conf.d are loaded in alpha-numerical order, if they exist. If the \$HOME/.config/containers/registries.conf is loaded, only the conf files under \$HOME/.config/containers/registries.conf.d are loaded in alpha-numerical order. Specified fields in a conf file will

overwrite any previous setting. Note that only files with the .conf suffix are loaded, other files and sub-directories are ignored.

For instance, setting the unqualified-search-registries in /etc/containers/registries.conf.d/myregistries.conf will overwrite previous settings in /etc/containers/registries.conf. The `[[registry]]` tables merged by overwriting existing items if the prefixes are identical while new ones are added.

All drop-in configuration files must be specified in the version 2 of the containers-registries.conf(5) format.

#### SEE ALSO

containers-registries.conf(5)

#### HISTORY

Mar 2020, Originally compiled by Valentin Rothberg [rothberg@redhat.com](mailto:rothberg@redhat.com)  
[?mailto:rothberg@redhat.com?](mailto:rothberg@redhat.com)

CONTAINERS-REGISTRIES.CONF.D(5)