



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'cryptsetup-luksUUID.8' command

\$ man cryptsetup-luksUUID.8

CRYPTSETUP-LUKSUUID(8) Maintenance Commands CRYPTSETUP-LUKSUUID(8)

NAME

cryptsetup-luksUUID - print or set the UUID of a LUKS device

SYNOPSIS

cryptsetup luksUUID [<options>] <device>

DESCRIPTION

Print the UUID of a LUKS device.

Set new UUID if --uuid option is specified.

<options> can be [--header, --uuid, --type, --disable-locks].

OPTIONS

--type <device-type>

Specifies required device type, for more info read BASIC ACTIONS section in cryptsetup(8).

--uuid <UUID>

Use the provided UUID for the luksFormat command instead of generating a new one. Changes the existing UUID when used with the luksUUID command.

The UUID must be provided in the standard UUID format, e.g.

12345678-1234-1234-1234-123456789abc.

--header <device or file storing the LUKS header>

Use a detached (separated) metadata device or file where the LUKS header is stored. This option allows one to store ciphertext and LUKS header on different devices.

For commands that change the LUKS header (e.g. `luksAddKey`), specify the device or file with the LUKS header directly as the LUKS device.

`--disable-locks`

Disable lock protection for metadata on disk. This option is valid only for LUKS2 and ignored for other formats.

WARNING: Do not use this option unless you run `cryptsetup` in a restricted environment where locking is impossible to perform (where `/run` directory cannot be used).

`--batch-mode, -q`

Suppresses all confirmation questions. Use with care!

If the `--verify-passphrase` option is not specified, this option also switches off the passphrase verification.

`--debug` or `--debug-json`

Run in debug mode with full diagnostic logs. Debug output lines are always prefixed by `#`.

If `--debug-json` is used, additional LUKS2 JSON data structures are printed.

`--version, -V`

Show the program version.

`--usage`

Show short option help.

`--help, -?`

Show help text and default parameters. == REPORTING BUGS

Report bugs at `cryptsetup` mailing list `<cryptsetup@lists.linux.dev>` or in Issues project section

`<https://gitlab.com/cryptsetup/cryptsetup/-/issues/new>`.

Please attach output of the failed command with `--debug` option added.

SEE ALSO

Cryptsetup FAQ

`<https://gitlab.com/cryptsetup/cryptsetup/wikis/FrequentlyAskedQuestions>`

`cryptsetup(8)`, `integritysetup(8)` and `veritysetup(8)`

Part of cryptsetup project <<https://gitlab.com/cryptsetup/cryptsetup/>>.

cryptsetup 2.6.0

2022-12-14

CRYPTSETUP-LUKSUUID(8)