

Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'ctanh.3' command

\$ man ctanh.3

CTANH(3)

Linux Programmer's Manual

CTANH(3)

NAME

ctanh, ctanhf, ctanhl - complex hyperbolic tangent

SYNOPSIS

#include <complex.h>

double complex ctanh(double complex z);

float complex ctanhf(float complex z);

long double complex ctanhl(long double complex z);

Link with -lm.

DESCRIPTION

These functions calculate the complex hyperbolic tangent of z.

The complex hyperbolic tangent function is defined mathematically as:

ctanh(z) = csinh(z) / ccosh(z)

VERSIONS

These functions first appeared in glibc in version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

?Interface

? Attribute ? Value ?

?ctanh(), ctanhf(), ctanhl() ? Thread safety ? MT-Safe ?

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

SEE ALSO

cabs(3), catanh(3), ccosh(3), csinh(3), complex(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

2017-09-15 CTANH(3)