



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'dcb-app.8' command

\$ man dcb-app.8

DCB-ETS(8) Linux DCB-ETS(8)

NAME

dcb-app - show / manipulate application priority table of the DCB (Data Center Bridging) subsystem

SYNOPSIS

dcb [OPTIONS] app { COMMAND | help }

dcb app { show | flush } dev DEV [default-prio] [ethtype-prio] [stream-port-prio] [dgram-port-prio] [port-prio] [dscp-prio]

dcb ets { add | del | replace } dev DEV [default-prio PRIO-LIST] [ethtype-prio ET-MAP] [stream-port-prio PORT-MAP] [dgram-port-prio PORT-MAP] [port-prio PORT-MAP] [dscp-prio DSCP-MAP]

PRIO-LIST := [PRIO-LIST] PRIO

ET-MAP := [ET-MAP] ET-MAPPING

ET-MAPPING := ET:PRIO

PORT-MAP := [PORT-MAP] PORT-MAPPING

PORT-MAPPING := PORT:PRIO

DSCP-MAP := [DSCP-MAP] DSCP-MAPPING

DSCP-MAPPING := { DSCP | all }:PRIO

ET := { 0x600 .. 0xffff }

PORT := { 1 .. 65535 }

DSCP := { 0 .. 63 }

PRIO := { 0 .. 7 }

DESCRIPTION

dcb app is used to configure APP table, or application priority table in the DCB (Data Center Bridging) subsystem. The APP table is used to assign priority to traffic based on value in one of several headers: EtherType, L4 destination port, or DSCP. It also allows configuration of port-default priority that is chosen if no other prioritization rule applies.

DCB APP entries are 3-tuples of selector, protocol ID, and priority. Selector is an enumeration that picks one of the prioritization name spaces. Currently it mostly corresponds to configurable parameters described below. Protocol ID is a value in the selector namespace. E.g. for EtherType selector, protocol IDs are the individual EtherTypes, for DSCP they are individual code points. The priority is the priority that should be assigned to traffic that matches the selector and protocol ID.

The APP table is a set of DCB APP entries. The only requirement is that duplicate entries are not added. Notably, it is valid to have conflicting priority assignment for the same selector and protocol ID. For example, the set of two APP entries (DSCP, 10, 1) and (DSCP, 10, 2), where packets with DSCP of 10 should get priority of both 1 and 2, form a well-defined APP table. The dcb app tool allows low-level management of the app table by adding and deleting individual APP 3-tuples through add and del commands. On the other other hand, the command replace does what one would typically want in this situation--first adds the new configuration, and then removes the obsolete one, so that only one prioritization is in effect for a given selector and protocol ID.

COMMANDS

show Display all entries with a given selector. When no selector is given, shows all APP table entries categorized per selector.

flush Remove all entries with a given selector. When no selector is given, removes all APP table entries.

add

`del` Add and, respectively, remove individual APP 3-tuples to and from the DCB APP table.

`replace`

Take the list of entries mentioned as parameter, and add those that are not present in the APP table yet. Then remove those entries, whose selector and protocol ID have been mentioned as parameter, but not with the exact same priority. This has the effect of, for the given selector and protocol ID, causing that the table only contains the priority (or priorities) given as parameter.

PARAMETERS

The following table shows parameters in a way that they would be used with `add`, `del` and `replace` commands. For `show` and `flush`, the parameter name is to be used as a simple keyword without further arguments.

`default-prio` PRIO-LIST

The priority to be used for traffic the priority of which is otherwise unspecified. The argument is a list of individual priorities. Note that `default-prio` rules are configured as triplets (EtherType, 0, PRIO). `dcb app` translates these rules to the symbolic name `default-prio` and back.

`ethtype-prio` ET-MAP

ET-MAP uses the array parameter syntax, see `dcb(8)` for details. Keys are EtherType values. Values are priorities to be assigned to traffic with the matching EtherType.

`stream-port-prio` PORT-MAP

`dgram-port-prio` PORT-MAP

`port-prio` PORT-MAP

PORT-MAP uses the array parameter syntax, see `dcb(8)` for details. Keys are L4 destination port numbers that match on, respectively, TCP and SCTP traffic, UDP and DCCP traffic, and either of those. Values are priorities that should be assigned to matching traffic.

`dscp-prio` DSCP-MAP

DSCP-MAP uses the array parameter syntax, see `dcb(8)` for details. Keys are DSCP points, values are priorities assigned to traffic with matching DSCP. DSCP points can be written either directly as numeric values, or using symbolic names specified in `/etc/iproute2/rt_dsfield` (however note that that file specifies full 8-bit dsfield values, whereas `dcb` app will only use the higher six bits). `dcb` app show will similarly format DSCP values as symbolic names if possible. The command line option `-N` turns the show translation off.

EXAMPLE & USAGE

Prioritize traffic with DSCP 0 to priority 0, 24 to 3 and 48 to 6:

```
# dcb app add dev eth0 dscp-prio 0:0 24:3 48:6
```

Add another rule to configure DSCP 24 to priority 2 and show the result:

sult:

```
# dcb app add dev eth0 dscp-prio 24:2
```

```
# dcb app show dev eth0 dscp-prio
```

```
dscp-prio 0:0 CS3:2 CS3:3 CS6:6
```

```
# dcb -N app show dev eth0 dscp-prio
```

```
dscp-prio 0:0 24:2 24:3 48:6
```

Reconfigure the table so that the only rule for DSCP 24 is for assignment of priority 4:

ment of priority 4:

```
# dcb app replace dev eth0 dscp-prio 24:4
```

```
# dcb app show dev eth0 dscp-prio
```

```
dscp-prio 0:0 24:4 48:6
```

Flush all DSCP rules:

```
# dcb app flush dev eth0 dscp-prio
```

```
# dcb app show dev eth0 dscp-prio
```

(nothing)

EXIT STATUS

Exit status is 0 if command was successful or a positive integer upon failure.

SEE ALSO

`dcb(8)`

REPORTING BUGS

Report any bugs to the Network Developers mailing list <net-dev@vger.kernel.org> where the development and maintenance is primarily done. You do not have to be subscribed to the list to send a message there.

AUTHOR

Petr Machata <me@pmachata.org>

iproute2

6 December 2020

DCB-ETS(8)