



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'dnf-repograph.8' command***

**\$ man dnf-repograph.8**

DNF-REPOGRAPH(8)          dnf-plugins-core          DNF-REPOGRAPH(8)

### NAME

dnf-repograph - DNF repograph Plugin

Output a full package dependency graph in dot format.

### SYNOPSIS

dnf repograph [<options>] dnf repo-graph [<options>]

### DESCRIPTION

repograph is a program that generates a full package dependency list from a repository and outputs it in dot format.

### Options

All general DNF options are accepted, see Options in dnf(8) for details.

**--repo <repoid>**

Specify repo ids to query, can be specified multiple times (default is all enabled).

### EXAMPLES

Output dependency list from all enabled repositories:

```
dnf repograph
```

Output dependency list from rawhide repository:

```
dnf repograph --repoid rawhide
```

Output dependency list from rawhide and koji repository:

```
dnf repo-graph --repoid rawhide --repoid koji
```

#### AUTHOR

See AUTHORS in your Core DNF Plugins distribution

#### COPYRIGHT

2023, Red Hat, Licensed under GPLv2+

4.3.0                      Mar 15, 2023                      DNF-REPOGRAPH(8)