



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'fc-conflist.1' command**

**\$ man fc-conflist.1**

FC-CONFLIST(1) FC-CONFLIST(1)

### NAME

fc-conflist - list the configuration files processed by Fontconfig

### SYNOPSIS

fc-conflist [ -Vh ]

[ --version ] [ --help ]

### DESCRIPTION

fc-conflist prints an annotated list of all the configuration files processed by Fontconfig.

The output is a '-' or '+' depending on whether the file is ignored or processed, a space, the file's path, a colon and space, and the description from the file or 'No description' if none is present.

The order of files looks like how fontconfig actually process them except one contains <include> element. In that case, it will be shown after processing all the sub directories where is targeted by <include>.

### OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

-V Show version of the program and exit.

-h Show summary of options.

### RETURN CODES

fc-conflist returns error code 0 for successful parsing, or 1 if any errors occurred or if at least one font face could not be opened.

#### AUTHOR

This manual page was updated by Akira TAGOH <akira@tagoh.org>.

Dec 21, 2021

FC-CONFLIST(1)