



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'fc-pattern.1' command***

**\$ man fc-pattern.1**

FC-PATTERN(1) FC-PATTERN(1)

### NAME

fc-pattern - parse and show pattern

### SYNOPSIS

```
fc-pattern [ -cdVh ] [ --config ] [ --default ] [ [ -f format ] [
--format format ] ] [ --version ] [ --help ]
[ pattern [ element... ] ]
```

### DESCRIPTION

fc-pattern parses pattern (empty pattern by default) and shows the parsed result. If --config is given, config substitution is performed on the pattern before being displayed. If --default is given, default substitution is performed on the pattern before being displayed.

If any elements are specified, only those are printed.

### OPTIONS

This program follows the usual GNU command line syntax, with long options starting with two dashes ('-'). A summary of options is included below.

- c Perform config substitution on pattern.
- d Perform default substitution on pattern.
- f Format output according to the format specifier format.
- V Show version of the program and exit.
- h Show summary of options.

pattern

Parses and displays pattern (uses empty pattern by default).

element

If set, the element property is displayed for parsed pattern.

#### SEE ALSO

FcNameParse(3) FcConfigSubstitute(3) FcDefaultSubstitute(3) FcPattern?

Print(3) FcPatternFormat(3) fc-cat(1) fc-cache(1) fc-list(1) fc-match(1) fc-query(1) fc-scan(1)

The fontconfig user's guide, in HTML format: </usr/share/doc/fontconfig/fontconfig-user.html>.

#### AUTHOR

This manual page was updated by Behdad Esfahbod <behdad@behdad.org>.

Apr 20, 2010

FC-PATTERN(1)