



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'flatpak-config.1' command

\$ man flatpak-config.1

FLATPAK CONFIG(1) flatpak config FLATPAK CONFIG(1)

NAME

flatpak-config - Manage configuration

SYNOPSIS

flatpak config [OPTION...]

flatpak config [OPTION...] --set KEY VALUE

flatpak config [OPTION...] --unset|--get KEY

DESCRIPTION

The flatpak config command shows or modifies the configuration of a flatpak installation. The following keys are supported:

languages

The languages that are included when installing Locale extensions.

The value is a semicolon-separated list of two-letter language codes, or one of the special values * or all. If this key is unset, flatpak defaults to including the extra-languages key and the current locale.

extra-languages

This key is used when languages is not set, and it defines extra locale extensions on top of the system configured languages. The value is a semicolon-separated list of locale identifiers (language, optional locale, optional codeset, optional modifier) as documented by setlocale(3) (for example, en;en_DK;zh_HK.big5hkscs;uz_UZ.utf8@cyrillic).

For configuration of individual remotes, see `flatpak-remote-modify(1)`.

For configuration of individual applications, see `flatpak-override(1)`.

OPTIONS

The following options are understood:

`-h, --help`

Show help options and exit.

`--list`

Print all keys and their values.

`--set`

Set key `KEY` to `VALUE`.

`--unset`

Unset key `KEY`.

`--get`

Print value of `KEY`.

`--user`

Configure per-user installation.

`--system`

Configure system-wide installation.

`--installation=NAME`

Configure the system-wide installation specified by `NAME` among those defined in `/etc/flatpak/installations.d/`. Using

`--installation=default` is equivalent to using `--system`.

`-v, --verbose`

Print debug information during command processing.

`--ostree-verbose`

Print OSTree debug information during command processing.

EXAMPLES

```
$ flatpak config --set languages "sv;en;fi"
```

SEE ALSO

`flatpak(1)`, `flatpak-remote-modify(1)`, `flatpak-override(1)`

`flatpak`

`FLATPAK CONFIG(1)`