



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'flatpak-installation.5' command

`$ man flatpak-installation.5`

FLATPAK INSTALLATION(5) flatpak installation FLATPAK INSTALLATION(5)

NAME

flatpak-installation - Configuration for an installation location

DESCRIPTION

flatpak can operate in system-wide or per-user mode. The system-wide data is located in `$prefix/var/lib/flatpak/`, and the per-user data is in `$HOME/.local/share/flatpak/`.

In addition to the default installation locations, more system-wide installations can be defined via configuration files `/etc/flatpak/installations.d/`, which must have the `.conf` extension and follow the format described below.

FILE FORMAT

The installation config file format is using the same `.ini` file format that is used for `systemd` unit files or application `.desktop` files.

[Installation ...]

All the configuration for the the installation location with name `NAME` is contained in the `[Installation "NAME"]` group.

The following keys are recognized:

Path (string)

The path for this installation. This key is mandatory.

DisplayName (string)

The name to use when showing this installation in the UI.

Priority (integer)

A priority for this installation.

StorageType (string)

The type of storage used for this installation. Possible values include: network, mmc, sdcard, harddisk.

EXAMPLES

[Installation "extra"]

Path=/location/of/sdcard

DisplayName=Extra Installation

StorageType=sdcard

flatpak

FLATPAK INSTALLATION(5)