



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'flatpak-remote-delete.1' command

\$ man flatpak-remote-delete.1

FLATPAK REMOTE-DELE(1) flatpak remote-delete FLATPAK REMOTE-DELE(1)

NAME

flatpak-remote-delete - Delete a remote repository

SYNOPSIS

flatpak remote-delete [OPTION...] NAME

DESCRIPTION

Removes a remote repository from the flatpak repository configuration.

NAME is the name of an existing remote.

Unless overridden with the --system, --user, or --installation options, this command uses either the default system-wide installation or the per-user one, depending on which has the specified REMOTE.

OPTIONS

The following options are understood:

-h, --help

Show help options and exit.

--user

Modify the per-user configuration.

--system

Modify the default system-wide configuration.

--installation=NAME

Modify a system-wide installation specified by NAME among those defined in /etc/flatpak/installations.d/. Using

--installation=default is equivalent to using --system.

--force

Remove remote even if its in use by installed apps or runtimes.

-v, --verbose

Print debug information during command processing.

--ostree-verbose

Print OSTree debug information during command processing.

EXAMPLES

```
$ flatpak --user remote-delete dried-raisins
```

SEE ALSO

flatpak(1), flatpak-remote-add(1), flatpak-remote-modify(1), flatpak-remotes(1)

flatpak

FLATPAK REMOTE-DELE(1)