Red Hat Enterprise Linux Release 9.2 Manual Pages on 'fold.1' command

$ man fold.1

FOLD(1)   User Commands   FOLD(1)

NAME

    fold - wrap each input line to fit in specified width

SYNOPSIS

    fold [OPTION]... [FILE]...

DESCRIPTION

    Wrap input lines in each FILE, writing to standard output.

    With no FILE, or when FILE is -, read standard input.

    Mandatory arguments to long options are mandatory for short options

    too.

    -b, --bytes

        count bytes rather than columns

    -c, --characters

        count characters rather than columns

    -s, --spaces

        break at spaces

    -w, --width=WIDTH

        use WIDTH columns instead of 80

    --help display this help and exit

    --version

        output version information and exit

AUTHOR

    Written by David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <https://www.gnu.org/software/coreutils/>

Report any translation bugs to <https://translationproject.org/team/>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc.   License GPLv3+: GNU

GPL version 3 or later <https://gnu.org/licenses/gpl.html>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation <https://www.gnu.org/software/coreutils/fold>

or available locally via: info '(coreutils) fold invocation'

GNU coreutils 8.32   January 2023   FOLD(1)