



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'fs.5' command

\$ man fs.5

FILESYSTEMS(5) Linux Programmer's Manual FILESYSTEMS(5)

NAME

filesystems - Linux filesystem types: ext, ext2, ext3, ext4, hpfs, iso9660, JFS, minix, msdos, ncfs nfs, ntfs, proc, Reiserfs, smb, sysv, umsdos, vfat, XFS, xiafs

DESCRIPTION

When, as is customary, the proc filesystem is mounted on /proc, you can find in the file /proc/filesystems which filesystems your kernel currently supports; see proc(5) for more details. There is also a legacy sysfs(2) system call (whose availability is controlled by the CONFIG_SYSFS_SYSCALL kernel build configuration option since Linux 3.15) that enables enumeration of the currently available filesystem types regardless of /proc availability and/or sanity.

If you need a currently unsupported filesystem, insert the corresponding kernel module or recompile the kernel.

In order to use a filesystem, you have to mount it; see mount(2) and mount(8).

The following list provides a short description of the available or historically available filesystems in the Linux kernel. See the kernel documentation for a comprehensive description of all options and limitations.

ext is an elaborate extension of the minix filesystem. It has been completely superseded by the second version of the

extended filesystem (ext2) and has been removed from the kernel (in 2.1.21).

ext2 is the high performance disk filesystem used by Linux for fixed disks as well as removable media. The second extended filesystem was designed as an extension of the extended filesystem (ext). See ext2(5).

ext3 is a journaling version of the ext2 filesystem. It is easy to switch back and forth between ext2 and ext3. See ext3(5).

ext4 is a set of upgrades to ext3 including substantial performance and reliability enhancements, plus large increases in volume, file, and directory size limits. See ext4(5).

hpfs is the High Performance Filesystem, used in OS/2. This filesystem is read-only under Linux due to the lack of available documentation.

iso9660 is a CD-ROM filesystem type conforming to the ISO 9660 standard.

High Sierra

Linux supports High Sierra, the precursor to the ISO 9660 standard for CD-ROM filesystems. It is automatically recognized within the iso9660 filesystem support under Linux.

Rock Ridge

Linux also supports the System Use Sharing Protocol records specified by the Rock Ridge Interchange Protocol. They are used to further describe the files in the iso9660 filesystem to a UNIX host, and provide information such as long filenames, UID/GID, POSIX permissions, and devices. It is automatically recognized within the iso9660 filesystem support under Linux.

JFS is a journaling filesystem, developed by IBM, that was integrated into Linux in kernel 2.4.24.

`minix` is the filesystem used in the Minix operating system, the first to run under Linux. It has a number of shortcomings, including a 64 MB partition size limit, short filenames, and a single timestamp. It remains useful for floppies and RAM disks.

`msdos` is the filesystem used by DOS, Windows, and some OS/2 computers. `msdos` filenames can be no longer than 8 characters, followed by an optional period and 3 character extension.

`ncpfs` is a network filesystem that supports the NCP protocol, used by Novell NetWare. It was removed from the kernel in 4.17.

To use `ncpfs`, you need special programs, which can be found at [?ftp://ftp.gwdg.de/pub/linux/misc/ncpfs?](ftp://ftp.gwdg.de/pub/linux/misc/ncpfs/).

`nfs` is the network filesystem used to access disks located on remote computers.

`ntfs` is the filesystem native to Microsoft Windows NT, supporting features like ACLs, journaling, encryption, and so on.

`proc` is a pseudo filesystem which is used as an interface to kernel data structures rather than reading and interpreting `/dev/kmem`. In particular, its files do not take disk space. See `proc(5)`.

`Reiserfs` is a journaling filesystem, designed by Hans Reiser, that was integrated into Linux in kernel 2.4.1.

`smb` is a network filesystem that supports the SMB protocol, used by Windows for Workgroups, Windows NT, and Lan Manager. See [?https://www.samba.org/samba/smbfs/?](https://www.samba.org/samba/smbfs/).

`sysv` is an implementation of the System V/Coherent filesystem for Linux. It implements all of Xenix FS, System V/386 FS, and Coherent FS.

`umsdos` is an extended DOS filesystem used by Linux. It adds capability for long filenames, UID/GID, POSIX permissions, and special files (devices, named pipes, etc.) under the DOS

filesystem, without sacrificing compatibility with DOS.

`tmpfs` is a filesystem whose contents reside in virtual memory.

Since the files on such filesystems typically reside in RAM, file access is extremely fast. See `tmpfs(5)`.

`vfat` is an extended FAT filesystem used by Microsoft Windows95 and Windows NT. `vfat` adds the capability to use long filenames under the MSDOS filesystem.

XFS is a journaling filesystem, developed by SGI, that was integrated into Linux in kernel 2.4.20.

`xiafs` was designed and implemented to be a stable, safe filesystem by extending the Minix filesystem code. It provides the basic most requested features without undue complexity. The `xiafs` filesystem is no longer actively developed or maintained. It was removed from the kernel in 2.1.21.

SEE ALSO

`fuse(4)`, `btrfs(5)`, `ext2(5)`, `ext3(5)`, `ext4(5)`, `nfs(5)`, `proc(5)`, `sysfs(5)`, `tmpfs(5)`, `ufs(5)`, `fsck(8)`, `mkfs(8)`, `mount(8)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux 2020-12-21 FILESYSTEMS(5)