



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'getwc\_unlocked.3' command**

### **\$ man getwc\_unlocked.3**

UNLOCKED\_STDIO(3)      Linux Programmer's Manual      UNLOCKED\_STDIO(3)

#### NAME

getc\_unlocked, getchar\_unlocked, putc\_unlocked, putchar\_unlocked - non?  
locking stdio functions

#### SYNOPSIS

```
#include <stdio.h>

int getc_unlocked(FILE *stream);

int getchar_unlocked(void);

int putc_unlocked(int c, FILE *stream);

int putchar_unlocked(int c);

void clearerr_unlocked(FILE *stream);

int feof_unlocked(FILE *stream);

int ferror_unlocked(FILE *stream);

int fileno_unlocked(FILE *stream);

int fflush_unlocked(FILE *stream);

int fgetc_unlocked(FILE *stream);

int fputc_unlocked(int c, FILE *stream);

size_t fread_unlocked(void *ptr, size_t size, size_t n,
                      FILE *stream);

size_t fwrite_unlocked(const void *ptr, size_t size, size_t n,
                      FILE *stream);

char *fgets_unlocked(char *s, int n, FILE *stream);

int fputs_unlocked(const char *s, FILE *stream);
```

```
#include <wchar.h>

wint_t getwc_unlocked(FILE *stream);

wint_t getwchar_unlocked(void);

wint_t fgetwc_unlocked(FILE *stream);

wint_t fputwc_unlocked(wchar_t wc, FILE *stream);

wint_t putwc_unlocked(wchar_t wc, FILE *stream);

wint_t putwchar_unlocked(wchar_t wc);

wchar_t *fgetws_unlocked(wchar_t *ws, int n, FILE *stream);

int fputws_unlocked(const wchar_t *ws, FILE *stream);
```

Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)):

```
getc_unlocked(), getchar_unlocked(), putc_unlocked(), putchar_un?
locked():

/* Since glibc 2.24: */ _POSIX_C_SOURCE >= 199309L

|| /* Glibc versions <= 2.23: */ _POSIX_C_SOURCE

|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE

clearerr_unlocked(), feof_unlocked(), ferror_unlocked(), fileno_un?
locked(), fflush_unlocked(), fgetc_unlocked(), fputc_unlocked(),
fread_unlocked(), fwrite_unlocked():

/* Glibc since 2.19: */ _DEFAULT_SOURCE

|| /* Glibc versions <= 2.19: */ _SVID_SOURCE || _BSD_SOURCE

fgets_unlocked(), fputs_unlocked(), getwc_unlocked(), getwchar_un?
locked(), fgetwc_unlocked(), fputwc_unlocked(), putwchar_unlocked(),
fgetws_unlocked(), fputws_unlocked():

_GNU_SOURCE
```

DESCRIPTION

Each of these functions has the same behavior as its counterpart with? out the "\_unlocked" suffix, except that they do not use locking (they do not set locks themselves, and do not test for the presence of locks set by others) and hence are thread-unsafe. See flockfile(3).

ATTRIBUTES

For an explanation of the terms used in this section, see at? tributes(7).

??

| Interface  | Attribute       | Value       |               |
|--|-----------------|-------------|---------------|
| ?? |                 |             |               |
| ?getc_unlocked(),  | ? Thread safety | ? MT-Safe   | race:stream ? |
| ?putc_unlocked(),  | ?               | ?           | ?             |
| ?clearerr_unlocked(),  | ?               | ?           | ?             |
| ?fflush_unlocked(),  | ?               | ?           | ?             |
| ?fgetc_unlocked(),   | ?               | ?           | ?             |
| ?fputc_unlocked(),   | ?               | ?           | ?             |
| ?fread_unlocked(),   | ?               | ?           | ?             |
| ?fwrite_unlocked(),  | ?               | ?           | ?             |
| ?fgets_unlocked(),   | ?               | ?           | ?             |
| ?fputs_unlocked(),   | ?               | ?           | ?             |
| ?getwc_unlocked(),   | ?               | ?           | ?             |
| ?fgetwc_unlocked(),  | ?               | ?           | ?             |
| ?fputwc_unlocked(),  | ?               | ?           | ?             |
| ?putwc_unlocked(),   | ?               | ?           | ?             |
| ?fgetws_unlocked(),  | ?               | ?           | ?             |
| ?fputws_unlocked()   | ?               | ?           | ?             |
| ?? |                 |             |               |
| ?getchar_unlocked(),   | ? Thread safety | ? MT-Unsafe | race:stdin ?  |
| ?getwchar_unlocked()   | ?               | ?           | ?             |
| ?? |                 |             |               |
| ?putchar_unlocked(),   | ? Thread safety | ? MT-Unsafe | race:stdout ? |
| ?putwchar_unlocked()   | ?               | ?           | ?             |
| ?? |                 |             |               |
| ?feof_unlocked(),  | ? Thread safety | ? MT-Safe   | ?             |
| ?ferror_unlocked(),  | ?               | ?           | ?             |
| ?fileno_unlocked()   | ?               | ?           | ?             |
| ?? |                 |             |               |

CONFORMING TO

The four functions getc\_unlocked(), getchar\_unlocked(), putc\_unlocked(), putchar\_unlocked() are in POSIX.1-2001 and POSIX.1-2008. The nonstandard \*\_unlocked() variants occur on a few UNIX systems, and

are available in recent glibc. They should probably not be used.

#### SEE ALSO

flockfile(3), stdio(3)

#### COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

2017-09-15

UNLOCKED\_STDIO(3)