



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'gnome-extensions.1' command

\$ man gnome-extensions.1

GNOME-EXTENSIONS(1) User Commands GNOME-EXTENSIONS(1)

NAME

gnome-extensions - Command line tool for managing GNOME extensions

SYNOPSIS

gnome-extensions help [COMMAND]
gnome-extensions version
gnome-extensions enable UUID
gnome-extensions disable UUID
gnome-extensions reset UUID
gnome-extensions info UUID
gnome-extensions show UUID
gnome-extensions list [OPTION...]
gnome-extensions prefs UUID
gnome-extensions create [OPTION...]
gnome-extensions pack [OPTION...]
gnome-extensions install [OPTION...] PACK
gnome-extensions uninstall UUID

DESCRIPTION

gnome-extensions is a utility that makes some common GNOME extensions operations available on the command line.

COMMON OPTIONS

All commands except for help and version handle the following options:

--quiet, -q

Do not print error messages

COMMANDS

help [COMMAND]

Displays a short synopsis of the available commands or provides detailed help on a specific command.

version

Prints the program version.

enable UUID

Enables the extension identified by UUID.

The command will not detect any errors from the extension itself, use the info command to confirm that the extension state is ENABLED.

If the extension is already enabled, the command will do nothing.

disable UUID

Disables the extension identified by UUID.

If the extension is not enabled, the command will do nothing.

reset UUID

Reset the extension identified by UUID.

The extension will be disabled in GNOME, but may be enabled by other sessions like GNOME Classic.

info UUID

Show details of the extension identified by UUID, including name, description and state.

show UUID

Synonym of info.

list [OPTION...]

Displays a list of installed extensions.

Options

--user

Include extensions installed in the user's \$HOME

--system

Include extensions installed in the system

--enabled

Include enabled extensions

--disabled

Include disabled extensions

--prefs

Only include extensions with preferences

--updates

Only include extensions with pending updates

-d, --details

Show some extra information for each extension

prefs UUID

Open the preference dialog of the extension identified by UUID.

create [OPTION...]

Creates a new extension from a template.

Options

--name=NAME

Set the user-visible name in the extension's metadata to

NAME

--description=DESC

Set the description in the extension's metadata to DESC

--uuid=UUID

Set the unique extension ID in the metadata to UUID

--template=TEMPLATE

Use TEMPLATE as base for the new extension

-i, --interactive

Prompt for any extension metadata that hasn't been provided

on the command line

pack [OPTION...] [SOURCE-DIRECTORY]

Creates an extension bundle that is suitable for publishing.

The bundle will always include the required files extension.js and

metadata.json, as well as the optional stylesheet.css and prefs.js

if found. Each additional source that should be included must be

specified with --extra-source.

If the extension includes one or more GSettings schemas, they can

either be placed in a schemas/ folder to be picked up automatically, or be specified with --schema.

Similarly, translations are included automatically when they are located in a po/ folder, otherwise the --podir option can be used to point to the correct directory. If no gettext domain is provided on the command line, the value of the gettext-domain metadata field is used if it exists, and the extension UUID if not.

All files are searched in SOURCE-DIRECTORY if specified, or the current directory otherwise.

Options

--extra-source=FILE

Additional source to include in the bundle

--schema=SCHEMA

A GSettings schema that should be compiled and included

--podir=PODIR

A directory with translations that should be compiled and included

--gettext-domain=DOMAIN

The gettext domain to use for translations

-f, --force

Overwrite an existing pack

-o, --out-dir=DIRECTORY

The directory where the pack should be created

install [OPTION...] PACK

Installs an extension from the bundle PACK.

The command unpacks the extension files and moves them to the expected location in the user's \$HOME, so that it will be loaded in the next session.

It is mainly intended for testing, not as a replacement for the extension website. As extensions have privileged access to the user's session, it is advised to never load extensions from untrusted sources without carefully reviewing their content.

Options

--force

Override an existing extension

uninstall UUID

Uninstalls the extension identified by UUID.

EXIT STATUS

On success 0 is returned, a non-zero failure code otherwise.

BUGS

The tool is part of the gnome-shell project, and bugs should be reported in its issue tracker at

<https://gitlab.gnome.org/GNOME/gnome-shell/issues>.

GNOME-EXTENSIONS-TOOL

August 2018

GNOME-EXTENSIONS(1)