



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'iconv_close.3' command

\$ man iconv_close.3

ICONV_CLOSE(3) Linux Programmer's Manual ICONV_CLOSE(3)

NAME

iconv_close - deallocate descriptor for character set conversion

SYNOPSIS

```
#include <iconv.h>

int iconv_close(iconv_t cd);
```

DESCRIPTION

The iconv_close() function deallocates a conversion descriptor cd previously allocated using iconv_open(3).

RETURN VALUE

When successful, the iconv_close() function returns 0. In case of error, it sets errno and returns -1.

VERSIONS

This function is available in glibc since version 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?iconv_close() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, SUSv2.

SEE ALSO

iconv(3), iconv_open(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

GNU

2017-09-15

ICONV_CLOSE(3)