



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'id.1' command

\$ man id.1

ID(1) User Commands ID(1)

NAME

id - print real and effective user and group IDs

SYNOPSIS

id [OPTION]... [USER]...

DESCRIPTION

Print user and group information for each specified USER, or (when USER omitted) for the current user.

-a ignore, for compatibility with other versions

-Z, --context

print only the security context of the process

-g, --group

print only the effective group ID

-G, --groups

print all group IDs

-n, --name

print a name instead of a number, for -ugG

-r, --real

print the real ID instead of the effective ID, with -ugG

-u, --user

print only the effective user ID

-z, --zero

delimit entries with NUL characters, not whitespace;

not permitted in default format

--help display this help and exit

--version

output version information and exit

Without any OPTION, print some useful set of identified information.

AUTHOR

Written by Arnold Robbins and David MacKenzie.

REPORTING BUGS

GNU coreutils online help: <<https://www.gnu.org/software/coreutils/>>

Report any translation bugs to <<https://translationproject.org/team/>>

COPYRIGHT

Copyright ? 2020 Free Software Foundation, Inc. License GPLv3+: GNU

GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>.

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

Full documentation <<https://www.gnu.org/software/coreutils/id>>

or available locally via: info '(coreutils) id invocation'

GNU coreutils 8.32

January 2023

ID(1)