



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'insights-client.8' command

\$ man insights-client.8

insights-client(8) insights-client(8)

NAME

insights-client - Red Hat Insights Client tool

SYNOPSIS

insights-client [options]

DESCRIPTION

insights-client is designed to help customers proactively resolve issues affecting business operations in Red Hat Enterprise Linux and Red Hat Cloud Infrastructure environments. View alerts or learn more at <https://console.redhat.com/insights/>. Due to the dynamic nature of this application, some options may become available that are not described in the manual. Please refer to the output of `--help` for the most up-to-date options, or view <https://access.redhat.com/articles/4099591> for more details.

OPTIONS

`-h, --help`

Show this help message and exit.

`--register`

Register host to the Red Hat Insights service.

`--unregister`

Unregister host from the Red Hat Insights service.

`--display-name=DISPLAYNAME`

Display name to use for this host. May be used during registra?

tion.

`--group=GROUP`

Group to add this host to. The group will be saved to the tags file.

`--retry=RETRIES`

Number of times to retry uploading. 180 seconds between tries.

`--validate`

Validate the contents of the denylist configuration.

`--quiet`

Only display error messages to stdout.

`--silent`

Display no messages to stdout.

`--enable-schedule`

Enable automatic scheduling.

`--disable-schedule`

Disable automatic scheduling.

`-c CONF, --conf=CONF`

Pass a custom config file.

`--compressor`

Specifies the compression algorithm to use. Choices are gz, bz2, xz, and none. Defaults to gz.

`--offline`

Collect locally only, do not connect to Insights and do not upload.

`--logging-file`

Specify a logfile other than the default.

`--payload=FILE`

Skip collection and upload a specified archive. Requires `--content-type`.

`--content-type=TYPE`

Content type of the archive specified with `--payload`.

`--diagnosis=ID`

Retrieve a remediation for this system.

--compliance

Scan the system with OpenSCAP and upload the report.

--check-results

Retrieve analysis results from the Red Hat Insights service.

--show-results

Display analysis results from the Red Hat Insights service.

--output-dir=DIR

Write the collection to a specified directory. Does not perform an upload.

--output-file=FILE

Write the collection to a specified file. Does not perform an upload.

--checkin

Perform a lightweight hourly check-in.

--list-specs

Show insights-client collection specs.

--compliance

Run a Compliance scan and upload.

--module MODULE, -m MODULE

Run a module from within the insights.client package. Analogous to "python -m MODULE". Use only as directed.

DEBUG OPTIONS

--version

Display version.

--test-connection

Test connectivity to Red Hat.

--force-reregister

Forcefully reregister this host to Red Hat. Will create a new ID for this host and create a new entry. Use only as directed.

--verbose

DEBUG output to stdout

--no-upload

Do not upload the archive.

--keep-archive

Do not delete archive after upload.

--support

Create a support logfile for Red Hat Insights.

--status

Check this host's registration status with Red Hat Insights.

--net-debug

Log network activity to console.

MOTD

A message will be displayed on login about insights-client if installed but has not yet been used at least once. To change or remove this message, edit the `/etc/insights-client/insights-client.motd` file.

SEE ALSO

[insights-client.conf\(5\)](#)

[Red Hat Insights](#)

[insights-client\(8\)](#)