



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'iswgraph.3' command

\$ man iswgraph.3

ISWGRAPH(3) Linux Programmer's Manual ISWGRAPH(3)

NAME

iswgraph - test for graphic wide character

SYNOPSIS

```
#include <wctype.h>

int iswgraph(wint_t wc);
```

DESCRIPTION

The `iswgraph()` function is the wide-character equivalent of the `isgraph(3)` function. It tests whether `wc` is a wide character belonging to the wide-character class "graph".

The wide-character class "graph" is a subclass of the wide-character class "print".

Being a subclass of the wide-character class "print", the wide-character class "graph" is disjoint from the wide-character class "cntrl".

The wide-character class "graph" is disjoint from the wide-character class "space" and therefore also disjoint from its subclass "blank".

The wide-character class "graph" contains all the wide characters from the wide-character class "print" except the space character. It therefore contains the wide-character classes "alnum" and "punct".

RETURN VALUE

The `iswgraph()` function returns nonzero if `wc` is a wide character belonging to the wide-character class "graph". Otherwise, it returns zero.

ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?iswgraph() ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of iswgraph() depends on the LC_CTYPE category of the cur?

rent locale.

SEE ALSO

isgraph(3), iswctype(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A

description of the project, information about reporting bugs, and the

latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

GNU

2015-08-08

ISWGRAPH(3)