



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'iswspace.3' command***

### ***\$ man iswspace.3***

ISWSPACE(3)            Linux Programmer's Manual            ISWSPACE(3)

#### NAME

iswspace - test for whitespace wide character

#### SYNOPSIS

```
#include <wctype.h>

int iswspace(wint_t wc);
```

#### DESCRIPTION

The `iswspace()` function is the wide-character equivalent of the `isspace(3)` function. It tests whether `wc` is a wide character belonging to the wide-character class "space".

The wide-character class "space" is disjoint from the wide-character class "graph" and therefore also disjoint from its subclasses "alnum", "alpha", "upper", "lower", "digit", "xdigit", "punct".

The wide-character class "space" contains the wide-character class "blank".

The wide-character class "space" always contains at least the space character and the control characters '\f', '\n', '\r', '\t', '\v'.

#### RETURN VALUE

The `iswspace()` function returns nonzero if `wc` is a wide character belonging to the wide-character class "space". Otherwise, it returns zero.

#### ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

??

?Interface ? Attribute ? Value ?

??

?iswspace() ? Thread safety ? MT-Safe locale ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C99.

NOTES

The behavior of iswspace() depends on the LC\_CTYPE category of the current locale.

SEE ALSO

isspace(3), iswctype(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.