



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'Inewusers.1' command

\$ man Inewusers.1

Inewusers(1) General Commands Manual Inewusers(1)

NAME

Inewusers - Create new user accounts

SYNOPSIS

Inewusers [OPTION]...

DESCRIPTION

Creates new user accounts using data read from standard input.

The input data consists of lines, each line has 7 colon-separated fields:

User name

Plaintext password

User ID

Inewusers refuses to create users with user ID 0 (the root user ID).

Group If this field is a valid group ID, it is interpreted as a group ID, otherwise as a group name. If the field is empty, a group name equal to user name is used.

If the specified group does not exist, it is automatically created. If the group is specified with a group ID, the created group has group name equal to the user name.

GECOS The GECOS field is traditionally used to store user's real name and other information.

Home directory

If this field is empty, a default specified by libuser configuration, or /home/username if libuser configuration does not specify a default, is used.

Login shell

If this field is empty, a default specified by libuser configuration is used.

Errors in user specifications are reported and processing continues on the next line.

OPTIONS

-f, --file=file

Read account data from file instead of standard input.

-i, --interactive

Ask all questions when connecting to the user database, even if default answers are set up in libuser configuration.

-M, --nocreatehome

Don't create home directories.

-n, --nocreatemail

Don't create mail spool files.

EXIT STATUS

The exit status is 0 on success, nonzero on fatal error. Errors in user specifications are not reflected in the exit status.

libuser

Jul 13 2008

Inewusers(1)