

Full credit is given to the above companies including the OS that this PDF file was generated!

# Red Hat Enterprise Linux Release 9.2 Manual Pages on 'logbf.3' command

# \$ man logbf.3 LOGB(3) Linux Programmer's Manual LOGB(3) NAME logb, logbf, logbl - get exponent of a floating-point value **SYNOPSIS** #include <math.h> double logb(double x); float logbf(float x); long double logbl(long double x); Link with -Im. Feature Test Macro Requirements for glibc (see feature\_test\_macros(7)): logb(): \_ISOC99\_SOURCE || \_POSIX\_C\_SOURCE >= 200112L || \_XOPEN\_SOURCE >= 500 || /\* Since glibc 2.19: \*/ \_DEFAULT\_SOURCE || /\* Glibc versions <= 2.19: \*/ \_BSD\_SOURCE || \_SVID\_SOURCE logbf(), logbl(): \_ISOC99\_SOURCE || \_POSIX\_C\_SOURCE >= 200112L || /\* Since glibc 2.19: \*/ \_DEFAULT\_SOURCE || /\* Glibc versions <= 2.19: \*/ \_BSD\_SOURCE || \_SVID\_SOURCE DESCRIPTION These functions extract the exponent from the internal floating-point representation of x and return it as a floating-point value. The inte?

ger constant FLT\_RADIX, defined in <float.h>, indicates the radix used

for the system's floating-point representation. If FLT\_RADIX is 2,

logb(x) is equal to floor(log2(x)), except that it is probably faster.

If x is subnormal, logb() returns the exponent x would have if it were normalized.

#### **RETURN VALUE**

On success, these functions return the exponent of x.

If x is a NaN, a NaN is returned.

If x is zero, then a pole error occurs, and the functions return

-HUGE\_VAL, -HUGE\_VALF, or -HUGE\_VALL, respectively.

If x is negative infinity or positive infinity, then positive infinity

is returned.

#### ERRORS

See math\_error(7) for information on how to determine whether an error

has occurred when calling these functions.

The following errors can occur:

Pole error: x is 0

A divide-by-zero floating-point exception (FE\_DIVBYZERO) is

raised.

These functions do not set errno.

#### ATTRIBUTES

For an explanation of the terms used in this section, see at?

tributes(7).

?Interface ? Attribute ? Value ?

?logb(), logbf(), logbl() ? Thread safety ? MT-Safe ?

CONFORMING TO

C99, POSIX.1-2001, POSIX.1-2008.

### SEE ALSO

ilogb(3), log(3)

## COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A

description of the project, information about reporting bugs, and the latest version of this page, can be found at https://www.kernel.org/doc/man-pages/.

2017-09-15 LOGB(3)