



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'lpasswd.1' command

\$ man lpasswd.1

`lpasswd(1)` General Commands Manual `lpasswd(1)`

NAME

`lpasswd` - Change group or user password

SYNOPSIS

`lpasswd` [OPTION]... [name]

DESCRIPTION

Changes password of user or group name.

If the name argument is not provided, username of the invoking user is

used; the name argument is ignored if `lpasswd` is run set-uid to a dif-

ferent user.

Entering an empty password (by pressing Enter) aborts the password set?

ting operation.

OPTIONS

`-F, --plainpassword-fd=fd`

Read password from file descriptor `fd`, terminated by end of file, `\r` or `\n`.

`-f, --password-fd=fd`

Read password hash from file descriptor `fd`, terminated by end of file, `\r` or `\n`.

`-g, --group`

Change password of group name. By default the password of user name is changed.

`-i, --interactive`

Ask all questions when connecting to the user database, even if default answers are set up in libuser configuration.

`-P, --plainpassword=password`

Set the password to password. Note that the password can be viewed while running `lpasswd` using tools such as `ps(1)`.

`-p, --password=encrypted`

Set the password to the password represented by the hash encrypted. Note that the hash can be viewed while running `lpasswd` using tools such as `ps(1)`.

EXIT STATUS

The exit status is 0 on success, nonzero on error.

libuser

Jan 12 2005

`lpasswd(1)`