



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'lpmove.8' command**

**\$ man lpmove.8**

lpmove(8)                    OpenPrinting                    lpmove(8)

### NAME

lpmove - move a job or all jobs to a new destination

### SYNOPSIS

lpmove [ -h server[:port] ] [ -E ] [ -U username ] job destination

lpmove [ -h server[:port] ] [ -E ] [ -U username ] source destination

### DESCRIPTION

lpmove moves the specified job or all jobs from source to destination.

job can be the job ID number or the old destination and job ID.

### OPTIONS

The lpmove command supports the following options:

-E Forces encryption when connecting to the server.

-U username

Specifies an alternate username.

-h server[:port]

Specifies an alternate server. Note: This option must occur before all others.

### EXAMPLES

Move job 123 from "oldprinter" to "newprinter":

```
lpmove 123 newprinter
```

or

```
lpmove oldprinter-123 newprinter
```

Move all jobs from "oldprinter" to "newprinter":

lpmove oldprinter newprinter

SEE ALSO

cancel(1), lp(1), lpr(1), lprm(1),

CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright ? 2007-2019 by Apple Inc.

2022-05-02

CUPS

lpmove(8)