



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## **Red Hat Enterprise Linux Release 9.2 Manual Pages on 'mailto.conf.5' command**

### **\$ man mailto.conf.5**

mailto.conf(5)            Apple Inc.            mailto.conf(5)

#### NAME

mailto.conf - configuration file for cups email notifier

#### DESCRIPTION

The mailto.conf file defines the local mail server and email notification preferences for CUPS.

Each line in the file can be a configuration directive, a blank line, or a comment. Configuration directives typically consist of a name and zero or more values separated by whitespace. The configuration directive name and values are case-insensitive. Comment lines start with the # character.

#### DIRECTIVES

Cc cc-address@domain.com

Specifies an additional recipient for all email notifications.

From from-address@domain.com

Specifies the sender of email notifications.

Sendmail sendmail command and options

Specifies the sendmail command to use when sending email notifications. Only one Sendmail or SMTPServer line may be present in the mailto.conf file. If multiple lines are present, only the last one is used.

SMTPServer servername

Specifies a SMTP server to send email notifications to. Only one

Sendmail or SMTPServer line may be present in the mailto.conf file. If multiple lines are present, only the last one is used.

Subject subject-prefix

Specifies a prefix string for the subject line of an email notification.

SEE ALSO

cupsd(8), CUPS Online Help (<http://localhost:631/help>)

COPYRIGHT

Copyright ? 2007-2019 by Apple Inc.

26 April 2019

CUPS

mailto.conf(5)