



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'man-recode.1' command

\$ man man-recode.1

MAN-RECODE(1) Manual pager utils MAN-RECODE(1)

NAME

man-recode - convert manual pages to another encoding

SYNOPSIS

man-recode -t to-code [--suffix=suffix|--in-place] [-dqhV] [filename]

DESCRIPTION

man-recode converts multiple manual pages from one encoding to another, guessing the appropriate input encoding for each one. It is useful when permanently recoding pages written in legacy character sets, or in build systems that need to recode a set of pages to a single common encoding (usually UTF-8) for installation. When converting many manual pages, this program is much faster than running `man --recode` or `manconv` on each page.

If an encoding declaration is found on the first line of a manual page, then that declaration is used as the input encoding for that page.

Failing that, the input encoding is guessed based on the file name.

Encoding declarations have the following form:

```
" -*- coding: UTF-8 -*-
```

or (if manual page preprocessors are also to be declared):

```
" t -*- coding: ISO-8859-1 -*-
```

OPTIONS

-t encoding, --to-code=encoding

Convert manual pages to encoding.

--suffix=suffix

Form each output file name by appending suffix to the input file name, after removing any compression extension.

--in-place

Overwrite each input file with the output, after removing any compression extension.

-q, --quiet

Do not issue error messages when the page cannot be converted.

-d, --debug

Print debugging information.

-h, --help

Print a help message and exit.

-V, --version

Display version information.

SEE ALSO

iconv(1), man(1), manconv(1)

BUGS

<https://savannah.nongnu.org/bugs/?group=man-db>

AUTHOR

Colin Watson (cjwatson@debian.org).

2.9.3

2020-06-22

MAN-RECODE(1)