



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'memmove.3' command

\$ man memmove.3

MEMMOVE(3) Linux Programmer's Manual MEMMOVE(3)

NAME

memmove - copy memory area

SYNOPSIS

```
#include <string.h>

void *memmove(void *dest, const void *src, size_t n);
```

DESCRIPTION

The memmove() function copies n bytes from memory area src to memory area dest. The memory areas may overlap: copying takes place as though the bytes in src are first copied into a temporary array that does not overlap src or dest, and the bytes are then copied from the temporary array to dest.

RETURN VALUE

The memmove() function returns a pointer to dest.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?memmove() ? Thread safety ? MT-Safe ?

??

CONFORMING TO

POSIX.1-2001, POSIX.1-2008, C89, C99, SVr4, 4.3BSD.

SEE ALSO

bcopy(3), bstring(3), memccpy(3), memcpy(3), strcpy(3), strncpy(3),
wmemmove(3)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A
description of the project, information about reporting bugs, and the
latest version of this page, can be found at
<https://www.kernel.org/doc/man-pages/>.

GNU

2017-03-13

MEMMOVE(3)