



Red Hat Enterprise Linux Release 9.2 Manual Pages on 'mmap2.2' command

\$ man mmap2.2

MMAP2(2) Linux Programmer's Manual MMAP2(2)

NAME

mmap2 - map files or devices into memory

SYNOPSIS

```
#include <sys/mman.h>

void *mmap2(void *addr, size_t length, int prot,
            int flags, int fd, off_t pgoffset);
```

DESCRIPTION

This is probably not the system call that you are interested in; instead, see `mmap(2)`, which describes the glibc wrapper function that invokes this system call.

The `mmap2()` system call provides the same interface as `mmap(2)`, except that the final argument specifies the offset into the file in 4096-byte units (instead of bytes, as is done by `mmap(2)`). This enables applications that use a 32-bit `off_t` to map large files (up to 2^{44} bytes).

RETURN VALUE

On success, `mmap2()` returns a pointer to the mapped area. On error, `-1` is returned and `errno` is set appropriately.

ERRORS

`EFAULT` Problem with getting the data from user space.

`EINVAL` (Various platforms where the page size is not 4096 bytes.) `offset * 4096` is not a multiple of the system page size.

`mmap2()` can also return any of the errors described in `mmap(2)`.

VERSIONS

`mmap2()` is available since Linux 2.3.31.

CONFORMING TO

This system call is Linux-specific.

NOTES

On architectures where this system call is present, the `glibc` `mmap()` wrapper function invokes this system call rather than the `mmap(2)` system call.

This system call does not exist on x86-64.

On ia64, the unit for offset is actually the system page size, rather than 4096 bytes.

SEE ALSO

`getpagesize(2)`, `mmap(2)`, `mremap(2)`, `msync(2)`, `shm_open(3)`

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.