



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'mq_getsetattr.2' command

\$ man mq_getsetattr.2

MQ_GETSETATTR(2) Linux Programmer's Manual MQ_GETSETATTR(2)

NAME

mq_getsetattr - get/set message queue attributes

SYNOPSIS

```
#include <sys/types.h>
```

```
#include <mqueue.h>
```

```
int mq_getsetattr(mqd_t mqdes, const struct mq_attr *newattr,  
                 struct mq_attr *oldattr);
```

Note: There is no glibc wrapper for this system call; see NOTES.

DESCRIPTION

Do not use this system call.

This is the low-level system call used to implement mq_getattr(3) and mq_setattr(3). For an explanation of how this system call operates, see the description of mq_setattr(3).

CONFORMING TO

This interface is nonstandard; avoid its use.

NOTES

Glibc does not provide a wrapper for this system call; call it using syscall(2). (Actually, never call it unless you are writing a C library!)

SEE ALSO

mq_getattr(3), mq_overview(7)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.

Linux

2020-08-13

MQ_GETSETATTR(2)