



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'msgcomm.1' command

\$ man msgcomm.1

MSGCOMM(1) User Commands MSGCOMM(1)

NAME

msgcomm - match two message catalogs

SYNOPSIS

msgcomm [OPTION] [INPUTFILE]...

DESCRIPTION

Find messages which are common to two or more of the specified PO files. By using the --more-than option, greater commonality may be requested before messages are printed. Conversely, the --less-than option may be used to specify less commonality before messages are printed (i.e. --less-than=2 will only print the unique messages).

Translations, comments and extracted comments will be preserved, but only from the first PO file to define them. File positions from all PO files will be cumulated.

Mandatory arguments to long options are mandatory for short options too.

Input file location:

INPUTFILE ...

input files

-f, --files-from=FILE

get list of input files from FILE

-D, --directory=DIRECTORY

add DIRECTORY to list for input files search

If input file is -, standard input is read.

Output file location:

-o, --output-file=FILE

write output to specified file

The results are written to standard output if no output file is specified or if it is -.

Message selection:

-<, --less-than=NUMBER

print messages with less than this many definitions, defaults to infinite if not set

->, --more-than=NUMBER

print messages with more than this many definitions, defaults to 1 if not set

-u, --unique

shorthand for --less-than=2, requests that only unique messages be printed

Input file syntax:

-P, --properties-input

input files are in Java .properties syntax

--stringtable-input

input files are in NeXTstep/GNUstep .strings syntax

Output details:

--color

use colors and other text attributes always

--color=WHEN

use colors and other text attributes if WHEN. WHEN may be 'always', 'never', 'auto', or 'html'.

--style=STYLEFILE

specify CSS style rule file for --color

-e, --no-escape

do not use C escapes in output (default)

-E, --escape

use C escapes in output, no extended chars

--force-po
 write PO file even if empty

-i, --indent
 write the .po file using indented style

--no-location
 do not write '#: filename:line' lines

-n, --add-location
 generate '#: filename:line' lines (default)

--strict
 write out strict Uniforum conforming .po file

-p, --properties-output
 write out a Java .properties file

--stringtable-output
 write out a NeXTstep/GNUstep .strings file

-w, --width=NUMBER
 set output page width

--no-wrap
 do not break long message lines, longer than the output page
 width, into several lines

-s, --sort-output
 generate sorted output

-F, --sort-by-file
 sort output by file location

--omit-header
 don't write header with 'msgid """ entry

Informative output:

-h, --help
 display this help and exit

-V, --version
 output version information and exit

AUTHOR

Written by Peter Miller.

Report bugs in the bug tracker at <<https://savannah.gnu.org/projects/gettext>> or by email to <bug-gettext@gnu.org>.

COPYRIGHT

Copyright ? 1995-2020 Free Software Foundation, Inc. License GPLv3+:

GNU GPL version 3 or later <<https://gnu.org/licenses/gpl.html>>

This is free software: you are free to change and redistribute it.

There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

The full documentation for msgcomm is maintained as a Texinfo manual.

If the info and msgcomm programs are properly installed at your site,

the command

`info msgcomm`

should give you access to the complete manual.

GNU gettext-tools 20200704

July 2020

MSGCOMM(1)