



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'npm-restart.1' command

\$ man npm-restart.1

NPM-RESTART(1)

NPM-RESTART(1)

NAME

npm-restart - Restart a package

Synopsis

npm restart [-- <args>]

Description

This restarts a project. It is equivalent to running npm run-script restart.

If the current project has a "restart" script specified in pack?

age.json, then the following scripts will be run:

1. prerestart
2. restart
3. postrestart

If it does not have a "restart" script specified, but it does have stop and/or start scripts, then the following scripts will be run:

1. prerestart
2. prestop
3. stop
4. poststop
5. prestart
6. start
7. poststart
8. postrestart

Configuration

ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as `npm start`, `npm stop`, `npm restart`, `npm test`, and `npm run-script` will still run their intended script if `ignore-scripts` is set, but they will not run any pre- or post-scripts.

script-shell

? Default: `'/bin/sh'` on POSIX systems, `'cmd.exe'` on Windows

? Type: null or String

The `shell` to use for scripts run with the `npm exec`, `npm run` and `npm init <package-spec>` commands.

See Also

? `npm help run-script`

? `npm help scripts`

? `npm help test`

? `npm help start`

? `npm help stop`

? `npm help restart`

February 2023

NPM-RESTART(1)