



## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'npm-stop.1' command***

**\$ man npm-stop.1**

NPM-STOP(1)

NPM-STOP(1)

NAME

npm-stop - Stop a package

Synopsis

```
npm stop [-- <args>]
```

Description

This runs a predefined command specified in the "stop" property of a package's "scripts" object.

Unlike with npm help start, there is no default script that will run if the "stop" property is not defined.

Example

```
{
  "scripts": {
    "stop": "node bar.js"
  }
}
```

```
}
```

```
npm stop
```

```
> npm@x.x.x stop
```

```
> node bar.js
```

```
(bar.js output would be here)
```

Configuration

ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as npm start, npm stop, npm restart, npm test, and npm run-script will still run their intended script if ignore-scripts is set, but they will not run any pre- or post-scripts.

#### script-shell

? Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows

? Type: null or String

The shell to use for scripts run with the npm exec, npm run and npm init <package-spec> commands.

#### See Also

? npm help run-script

? npm help scripts

? npm help test

? npm help start

? npm help restart

February 2023

NPM-STOP(1)