



*Full credit is given to the above companies including the OS that this PDF file was generated!*

## ***Red Hat Enterprise Linux Release 9.2 Manual Pages on 'npm-test.1' command***

**\$ man npm-test.1**

NPM-TEST(1)

NPM-TEST(1)

NAME

npm-test - Test a package

Synopsis

npm test [-- <args>]

aliases: tst, t

Description

This runs a predefined command specified in the "test" property of a package's "scripts" object.

Example

```
{
  "scripts": {
    "test": "node test.js"
  }
}
```

```
npm test
```

```
> npm@x.x.x test
```

```
> node test.js
```

```
(test.js output would be here)
```

Configuration

ignore-scripts

? Default: false

? Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as `npm start`, `npm stop`, `npm restart`, `npm test`, and `npm run-script` will still run their intended script if `ignore-scripts` is set, but they will not run any pre- or post-scripts.

#### script-shell

? Default: `'/bin/sh'` on POSIX systems, `'cmd.exe'` on Windows

? Type: null or String

The `shell` to use for scripts run with the `npm exec`, `npm run` and `npm init <package-spec>` commands.

#### See Also

? `npm help run-script`

? `npm help scripts`

? `npm help start`

? `npm help restart`

? `npm help stop`

February 2023

NPM-TEST(1)