



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'npm-view.1' command

\$ man npm-view.1

NPM-VIEW(1) NPM-VIEW(1)

NAME

npm-view - View registry info

Synopsis

```
npm view [<package-spec>] [<field>[.subfield]...]
```

aliases: info, show, v

Description

This command shows data about a package and prints it to stdout.

As an example, to view information about the connect package from the registry, you would run:

```
npm view connect
```

The default version is "latest" if unspecified.

Field names can be specified after the package descriptor. For example, to show the dependencies of the ronn package at version 0.3.5, you could do the following:

```
npm view ronn@0.3.5 dependencies
```

You can view child fields by separating them with a period. To view the git repository URL for the latest version of npm, you would run the following command:

```
npm view npm repository.url
```

This makes it easy to view information about a dependency with a bit of shell scripting. For example, to view all the data about the version of opts that ronn depends on, you could write the following:

```
npm view opts@$(npm view ronn dependencies.opts)
```

For fields that are arrays, requesting a non-numeric field will return all of the values from the objects in the list. For example, to get all the contributor email addresses for the express package, you would run:

```
npm view express contributors.email
```

You may also use numeric indices in square braces to specifically select an item in an array field. To just get the email address of the first contributor in the list, you can run:

```
npm view express contributors[0].email
```

Multiple fields may be specified, and will be printed one after another. For example, to get all the contributor names and email addresses, you can do this:

```
npm view express contributors.name contributors.email
```

"Person" fields are shown as a string if they would be shown as an object. So, for example, this will show the list of npm contributors in the shortened string format. (See [package.json /configuring-npm/package-json](#) for more on this.)

```
npm view npm contributors
```

If a version range is provided, then data will be printed for every matching version of the package. This will show which version of jsdom was required by each matching version of yui3:

```
npm view yui3@'>0.5.4' dependencies.jsdom
```

To show the connect package version history, you can do this:

```
npm view connect versions
```

Configuration

json

? Default: false

? Type: Boolean

Whether or not to output JSON data, rather than the normal output.

? In npm pkg set it enables parsing set values with `JSON.parse()` before saving them to your package.json.

Not supported by all npm commands.

workspace

? Default:

? Type: String (can be set multiple times)

Enable running a command in the context of the configured workspaces of the current project while filtering by running only the workspaces defined by this configuration option.

Valid values for the workspace config are either:

? Workspace names

? Path to a workspace directory

? Path to a parent workspace directory (will result in selecting all workspaces within that folder)

When set for the npm init command, this may be set to the folder of a workspace which does not yet exist, to create the folder and set it up as a brand new workspace within the project.

This value is not exported to the environment for child processes.

workspaces

? Default: null

? Type: null or Boolean

Set to true to run the command in the context of all configured workspaces.

Explicitly setting this to false will cause commands like install to ignore workspaces altogether. When not set explicitly:

? Commands that operate on the node_modules tree (install, update, etc.) will link workspaces into the node_modules folder. - Commands that do other things (test, exec, publish, etc.) will operate on the root project, unless one or more workspaces are specified in the workspace config.

This value is not exported to the environment for child processes.

include-workspace-root

? Default: false

? Type: Boolean

Include the workspace root when workspaces are enabled for a command.

When false, specifying individual workspaces via the workspace config, or all workspaces via the workspaces flag, will cause npm to operate

only on the specified workspaces, and not on the root project.

This value is not exported to the environment for child processes.

Output

If only a single string field for a single version is output, then it will not be colorized or quoted, to enable piping the output to another command. If the field is an object, it will be output as a JavaScript object literal.

If the `--json` flag is given, the outputted fields will be JSON.

If the version range matches multiple versions then each printed value will be prefixed with the version it applies to.

If multiple fields are requested, then each of them is prefixed with the field name.

See Also

? npm help "package spec"

? npm help search

? npm help registry

? npm help config

? npm help npmrc

? npm help docs

February 2023

NPM-VIEW(1)