



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'nvme-wdc-get-error-recovery-log.1' command

\$ man nvme-wdc-get-error-recovery-log.1

NVME-WDC-GET-ERRO(1) NVMe Manual NVME-WDC-GET-ERRO(1)

NAME

nvme-wdc-get-error-recovery-log - Send NVMe WDC get-error-recovery-log plugin command, return parsed log output

SYNOPSIS

```
nvme wdc get-error-recovery-log <device> [--output-format=<normal|json>
-o <normal|json>]
```

DESCRIPTION

For the NVMe device given, send a WDC plugin get-error-recovery-log command and output the error recovery log data. The --output-format option will format the output as specified.

The <device> parameter is mandatory and may be either the NVMe character device (ex: /dev/nvme0).

This will only work on WDC devices supporting this log page. Results for any other device are undefined.

On success it returns the parsed error recovery log page data, error code otherwise.

OPTIONS

-o <format>, --output-format=<format>

Set the reporting format to normal, or json. Only one output format can be used at a time. Default is normal.

EXAMPLES

? Has the program issue WDC get-error-recovery-log plugin command :

```
# nvme wdc get-error-recovery-log /dev/nvme0
```

NVME

Part of the nvme-user suite.

NVMe 06/23/2023 NVME-WDC-GET-ERRO(1)