



Full credit is given to the above companies including the OS that this PDF file was generated!

Red Hat Enterprise Linux Release 9.2 Manual Pages on 'openlog.3' command

\$ man openlog.3

SYSLOG(3) Linux Programmer's Manual SYSLOG(3)

NAME

closelog, openlog, syslog, vsyslog - send messages to the system logger

SYNOPSIS

```
#include <syslog.h>

void openlog(const char *ident, int option, int facility);

void syslog(int priority, const char *format, ...);

void closelog(void);

void vsyslog(int priority, const char *format, va_list ap);
```

Feature Test Macro Requirements for glibc (see feature_test_macros(7)):

vsyslog():

Since glibc 2.19:

 _DEFAULT_SOURCE

Glibc 2.19 and earlier:

 _BSD_SOURCE

DESCRIPTION

openlog()

openlog() opens a connection to the system logger for a program.

The string pointed to by ident is prepended to every message, and is typically set to the program name. If ident is NULL, the program name is used. (POSIX.1-2008 does not specify the behavior when ident is NULL.)

The option argument specifies flags which control the operation of

`openlog()` and subsequent calls to `syslog()`. The facility argument establishes a default to be used if none is specified in subsequent calls to `syslog()`. The values that may be specified for option and facility are described below.

The use of `openlog()` is optional; it will automatically be called by `syslog()` if necessary, in which case `ident` will default to `NULL`.

`syslog()` and `vsyslog()`

`syslog()` generates a log message, which will be distributed by `syslogd(8)`.

The priority argument is formed by ORing together a facility value and a level value (described below). If no facility value is ORed into priority, then the default value set by `openlog()` is used, or, if there was no preceding `openlog()` call, a default of `LOG_USER` is employed.

The remaining arguments are a format, as in `printf(3)`, and any arguments required by the format, except that the two-character sequence `%m` will be replaced by the error message string `strerror(errno)`. The format string need not include a terminating newline character.

The function `vsyslog()` performs the same task as `syslog()` with the difference that it takes a set of arguments which have been obtained using the `stdarg(3)` variable argument list macros.

`closelog()`

`closelog()` closes the file descriptor being used to write to the system logger. The use of `closelog()` is optional.

Values for option

The option argument to `openlog()` is a bit mask constructed by ORing together any of the following values:

`LOG_CONS` Write directly to the system console if there is an error or while sending to the system logger.

`LOG_NDELAY` Open the connection immediately (normally, the connection is opened when the first message is logged). This may be useful, for example, if a subsequent `chroot(2)` would make the pathname used internally by the logging facility unreachable.

LOG_NOWAIT Don't wait for child processes that may have been created while logging the message. (The GNU C library does not create a child process, so this option has no effect on Linux.)

LOG_ODELAY The converse of LOG_NDELAY; opening of the connection is delayed until syslog() is called. (This is the default, and need not be specified.)

LOG_PERROR (Not in POSIX.1-2001 or POSIX.1-2008.) Also log the message to stderr.

LOG_PID Include the caller's PID with each message.

Values for facility

The facility argument is used to specify what type of program is logging the message. This lets the configuration file specify that messages from different facilities will be handled differently.

LOG_AUTH security/authorization messages

LOG_AUTHPRIV security/authorization messages (private)

LOG_CRON clock daemon (cron and at)

LOG_DAEMON system daemons without separate facility value

LOG_FTP ftp daemon

LOG_KERN kernel messages (these can't be generated from user processes)

LOG_LOCAL0 through LOG_LOCAL7

reserved for local use

LOG_LPR line printer subsystem

LOG_MAIL mail subsystem

LOG_NEWS USENET news subsystem

LOG_SYSLOG messages generated internally by syslogd(8)

LOG_USER (default)

generic user-level messages

LOG_UUCP UUCP subsystem

Values for level

This determines the importance of the message. The levels are, in order of decreasing importance:

LOG_EMERG system is unusable
 LOG_ALERT action must be taken immediately
 LOG_CRIT critical conditions
 LOG_ERR error conditions
 LOG_WARNING warning conditions
 LOG_NOTICE normal, but significant, condition
 LOG_INFO informational message
 LOG_DEBUG debug-level message

The function setlogmask(3) can be used to restrict logging to specified levels only.

ATTRIBUTES

For an explanation of the terms used in this section, see attributes(7).

??

?Interface ? Attribute ? Value ?

??

?openlog(), closelog() ? Thread safety ? MT-Safe ?

??

?syslog(), vsyslog() ? Thread safety ? MT-Safe env locale ?

??

CONFORMING TO

The functions openlog(), closelog(), and syslog() (but not vsyslog()) are specified in SUSv2, POSIX.1-2001, and POSIX.1-2008.

POSIX.1-2001 specifies only the LOG_USER and LOG_LOCAL* values for facility. However, with the exception of LOG_AUTHPRIV and LOG_FTP, the other facility values appear on most UNIX systems.

The LOG_PERROR value for option is not specified by POSIX.1-2001 or POSIX.1-2008, but is available in most versions of UNIX.

NOTES

The argument ident in the call of openlog() is probably stored as-is. Thus, if the string it points to is changed, syslog() may start prepending the changed string, and if the string it points to ceases to exist, the results are undefined. Most portable is to use a string

constant.

Never pass a string with user-supplied data as a format, use the fol?

lowing instead:

```
syslog(priority, "%s", string);
```

SEE ALSO

journalctl(1), logger(1), setlogmask(3), syslog.conf(5), syslogd(8)

COLOPHON

This page is part of release 5.10 of the Linux man-pages project. A

description of the project, information about reporting bugs, and the

latest version of this page, can be found at

<https://www.kernel.org/doc/man-pages/>.

Linux

2017-09-15

SYSLOG(3)